Appendix N: Distance Required to be Exceeded by an Ephemeral Drainage to Exclude a Stormwater Outfall from Priority Status ¹

| | | | | Ve | getated Eph | nemeral Dra | ainage | | | | | |
|------------|-----------|--|------------|-------|-------------|-------------|-------------|-------------|-----|-----|-----|------|
| Sw | ale | Water Quality Volume Discharge Rate(cfs) | | | | | | | | | | |
| Width (ft) | Grade (%) | 0.2 | 0.45 | 0.9 | 1.3 | 1.8 | 2.2 | 2.7 | 3.1 | 3.6 | 4 | 4.4 |
| 15 | 0.5 | 150 | 150 | 150 | 150 | 150 | 175 | 200 | 225 | 250 | 250 | 275 |
| | 1 | 150 | 150 | 150 | 175 | 200 | 225 | 250 | 275 | 300 | 325 | 3 50 |
| | 1.5 | 150 | 150 | 150 | 175 | 225 | 250 | 300 | 325 | 350 | - | - |
| | 2 | 150 | 150 | 150 | 200 | 250 | 275 | 325 | - | - | - | - |
| | 2.5 | 150 | 150 | 175 | 225 | 275 | 300 | - | - | - | - | - |
| | 3 | 150 | 150 | 175 | 225 | 275 | 325 | - | - | - | - | - |
| | 4 | 150 | 150 | 200 | 250 | 325 | - | - | - | - | - | - |
| | 5 | 150 | 150 | 200 | 275 | - | - | - | - | - | - | - |
| 10 | 0.5 | 150 | 150 | 150 | 150 | 200 | 225 | 250 | 275 | 300 | 325 | 3 50 |
| | 1 | 150 | 150 | 175 | 200 | 250 | 275 | 325 | 350 | - | - | - |
| | 1.5 | 150 | 150 | 175 | 225 | 275 | 325 | - | - | - | - | - |
| | 2 | 150 | 150 | 200 | 250 | 325 | - | - | - | - | - | - |
| | 2.5 | 150 | 150 | 225 | 275 | - | - | - | - | - | - | - |
| | 3 | 150 | 150 | 225 | 300 | - | - | = | - | - | - | - |
| | 4 | 150 | 150 | 250 | - | - | - | = | - | - | - | - |
| | 5 | 150 | 175 | 275 | | | | | - | | | - |
| 5 | 0.5 | 150 | 150 | 175 | 225 | 275 | 325 | 375 | 450 | 500 | 550 | - |
| | 1 | 150 | 150 | 225 | 275 | 3 50 | - | - | - | - | - | - |
| | 1.5 | 150 | 175 | 275 | 325 | - | - | - | - | - | - | - |
| | 2 | 150 | 200 | 300 | - | - | - | - | - | - | - | - |
| | 2.5 | 150 | 200 | 325 | - | - | - | - | - | - | - | - |
| | 3 4 | 150 | 225 | - | - | - | - | - | - | - | - | - |
| | 5 | 150 150 | 250 275 | - | - | - | - | - | - | - | - | - |
| 2 | 0.5 | 150 | 175 | 250 | 350 | 450 | 550 | 650 | 725 | - | - | - |
| | 1 | 150 | 225 | 300 | 375 | 430 | - | - | 723 | - | - | - |
| | 1.5 | 150 | 250 | 500 | - | _ | | _ | | _ | _ | |
| | 2 | 175 | 275 | _ | _ | - | _ | _ | _ | _ | _ | _ |
| | 2.5 | 200 | 300 | _ | _ | _ | _ | _ | _ | _ | _ | _ |
| | 3 | 200 | - | _ | _ | _ | _ | _ | _ | _ | _ | _ |
| | 4 | 225 | _ | _ | _ | _ | _ | _ | _ | _ | _ | _ |
| | 5 | 250 | _ | _ | _ | | _ | _ | _ | _ | _ | _ |
| 0 | 0.5 | 150 | 250 | 450 | 550 | 725 | 800 | 950 | - | - | - | |
| | 1 | 175 | 300 | 500 | - | - | - | | _ | - | - | - |
| | 1.5 | 225 | 325 | - | - | - | - | - | - | - | - | - |
| | 2 | 225 | - | - | - | - | - | - | - | - | - | - |
| | 2.5 | 275 | - | - | - | - | - | - | - | - | - | - |
| | 3 | 275 | - | - | - | - | - | - | - | - | - | - |
| | 4 | | - | - | - | - | - | - | - | - | - | - |
| | 5 | - | - | - | - | - | - | - | - | - | - | - |
| | | • | | Non-V | egetated Er | mphemeral | Drainage | | | | | |
| Sw | ale | | | | | • | olume Disch | arge Rate(c | fs) | | | |
| Width (ft) | Grade (%) | 0.2 | 0.45 | 0.9 | 1.3 | 1.8 | 2.2 | 2.7 | 3.1 | 3.6 | 4 | 4.4 |
| All | All | - | - | - | - | - | - | - | - | - | - | - |
| | | | | | | | | | | | | |

 $^{^{1}}$ Distances given in feet. A dash indicates no distance is acceptable for excluding the Stormwater Outfall as a priority.