


PROJECT NO.	SHEET NO.
NH-80-1(169)	1
CONTROL NO.	51276A
CONTROL NO.	
CONTROL NO.	

STATE OF NEBRASKA
DEPARTMENT OF TRANSPORTATION
PLANS FOR CONSTRUCTION


SIDNEY WB REST AREA BUILDINGS

CHEYENNE COUNTY


Preliminary




ENGINEER
(NDOT COORDINATING PROFESSIONAL)




CIVIL ENGINEER




ARCHITECT
(COORDINATING PROFESSIONAL)




LANDSCAPE ARCHITECT



CIVIL ENGINEER
(STRUCTURAL)



MECHANICAL ENGINEER



ELECTRICAL ENGINEER

GENERAL

- G0.00 Title Sheet & Drawing Index
- G0.01 General Notes, Symbols & Abbreviations
- G0.10 Code Compliance Plan
- G0.20 ADA Details
- G0.21 ADA Details

CIVIL

- C1.01A Sanitary Sewer Plan & Profiles
- C2.01A Sanitary Sewer Plan & Profiles
- C3.01A Potable Water Plan & Profiles

LANDSCAPE ARCHITECTURAL

- L1.01 Site Existing Conditions/ Demolition Plan
- L2.01 Site Layout Plan
- L3.01 Site Grading Plan
- L4.01 Tree/ Turf Site Planting Plan & Shrub/ Ornamental Grass Site Planting Plan
- L5.01 Site Irrigation Plan
- L6.01 Site Details

ARCHITECTURAL

- A0.00 Wall Type Schedule & Details
- A1.11 First Floor Plan
- A1.12 Concrete Floor Slab Control Joint Plan
- A1.21 First Floor Reflected Ceiling Plan
- A1.30 Roof Plan
- A2.10 East and South Exterior Elevations
- A2.11 West and North Exterior Elevations
- A3.10 Building Cross Sections
- A4.10 Wall Sections
- A4.11 Wall Sections
- A6.10 Enlarged Interior/Exterior Elevations & Schedule
- A6.40 Door Schedule, Door Types, Frame Types & Casework Sections
- A7.10 Plan and Section Details

INTERIOR FINISHES

- F1.11 First Floor Finishes Plan

STRUCTURAL

- S0.00 Structural Notes
- S1.01 Footing & Foundation Plan
- S2.01 Roof Framing Plan
- S3.01 Structural Details

MECHANICAL

- M0.00 Mechanical Abbreviations, Symbols & Notes
- M1.01 First Floor HVAC Plan
- M2.01 Mechanical Details
- M3.01 Mechanical Schedules

PLUMBING


- P1.01 Below Floor Plumbing Plan
- P1.02 First Floor Plumbing Plan
- P2.01 Plumbing Details
- P3.01 Riser Diagrams
- P4.01 Plumbing Schedules

PLUMBING / MECHANICAL

- PM1.01 Mechanical Sections

ELECTRICAL

- E0.00 Electrical Abbreviations, Symbols Legend & Electrical Details
- E0.01 Site Electrical Utilities Plan
- E1.11 Electrical Plans



VICINITY MAP
SCALE: NOT TO SCALE

SCHEDULE OF QUANTITIES

ITEM	QUANTITY	UNITS
REST AREA	1.000	LUMP SUM

WORK ON THIS PROJECT IS AUTHORIZED PURSUANT TO THE CONDITIONS STIPULATED IN THE ARMY CORPS OF ENGINEERS GENERAL / NATIONWIDE / INDIVIDUAL PERMIT

THE 2017 EDITION OF THE NEBRASKA STANDARD SPECIFICATIONS AND THE SPECIAL PROVISIONS APPLY TO THIS PROJECT.

THE WORK ON THIS PROJECT CONSISTS OF GROUPS

8A - BUILDING

GROUPS - 8A	ARE INCLUDED
IN THE LETTING OF	
GROUPS	ARE INCLUDED
IN THE LETTING OF	
GROUPS	ARE INCLUDED
IN THE LETTING OF	

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.:
Control No.: 51276A
May 15, 2023

Preliminary

Title Sheet & Drawing Index


G0.00

MATERIAL SYMBOLS


EARTHWORKS




CONCRETE




MASONRY




STONE



METAL




WOOD



GLASS



INSULATION



FINISHES




PARTITION INDICATIONS




SPECIAL FINISH FACE

































ELEVATION INDICATIONS



GLASS



REFERENCE SYMBOLS



STANDARD ABBREVIATIONS

AE	ARCHITECT/ENGINEER	CONTR	CONTRACTOR	GORL	GUARD RAIL	MTG	MEETING	SLS	SUB-FLOOR LEVELING SYSTEM
AB	ANCHOR BOLT	CORR	CORRIDOR	GENL	GENERAL CONTRACTOR	MTL	METAL	SLV	SUB-FLOOR LEVELING SYSTEM
ABBR	ABBREVIATE	COVER	COVER PLATE	GENL CONTR	GENERAL CONTRACTOR	MTR	MORTAR	SM	SHEET METAL
AC	AC	CR	CR	GL	GLASS	MULL	MULLION	SMLS	SEAMLESS
AC RES	AIR CONDITIONING	CRPS	COMPRESSIBLE	GLB	GLASS BLOCK	MULT	MULTIPLE	SP	SPECIAL
ACOUS	ACOUSTICAL	CRUF	CIRCUMFERENCE	GLU	GLUE LAMINATED	N	NORTH	SPCL	SPECIFICATION
ACOUS INSUL	ACOUSTICAL INSULATION	CRS	COLD ROLLED STEEL	GLZ	GLAZING	NA	NOT APPLICABLE	SPKRL	SPEAKER
ACOUS INL	ACOUSTICAL PANELS	CSC	CASEMENT	GLZ CMU	GLAZED CONCRETE MASONRY UNIT	NEG	NEGATIVE	SPKL	SPEAKER
ACOUS PLAS	ACOUSTICAL PLASTER	CSK	COUNTERSINK	GND	GROUND	NF	NEAR FACE	SPRT	SUPPORT
ACOUS TILE	ACOUSTICAL TILE	CSW	CASEWORK	GR	GRADE	NOT	NOT IN	SQ	SQUARE
ACT	ACTUAL	CSWK	CASEWORK	GR BM	GRADE BEAM	NO	NUMBER	SQYD	SQUARE YARD
AD	AREA DRAIN	CT	CABLE TELEVISION	GRT	GRATING	OD	OUT OF	SSK	SERVICE SINK
ADG	AUTOMATIC DOOR CLOSER	CUB	CUBICLE	QUT	OUT TO OUT	OA	OVERALL	ST	STAIN
ADDL	ADDITIONAL	CUR	CURRENT	H	HANDICAP	OC	ON CENTER	STAG	STAIR
ADM	ADJUSTABLE	DEPT	DEPARTMENT	H&W	HOT AND COLD WATER	OF	OWNER FURNISHED CONTRACTOR INSTALL	STC	SOUND TRANSMISSION CLASS
ADJ	ADJUSTABLE	DET	DETAIL	HR	HANDICAP	OFI	OWNER FURNISHED-OWNER INSTALLED	STD	STANDARD
AFF	ACCESS FLOOR	DR	DRAIN	H&W	HOT AND COLD WATER	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AFG	ABOVE FINISHED GRADE	DRF	DRAIN FABRIC	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL JST	STEEL JOIST
AFS	AGGREGATE	DRH	DOUBLE HUNG	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL PLT	STEEL PLATE
AGGR	AGGREGATE	DI	DIAMETER	HR	HANDICAP	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AHL	AIR HANDLING UNIT	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AHL	AIR HANDLING UNIT	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ALD	ALUMINUM DOOR	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ALT	ALTERNATE	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ALLM	ALUMINUM	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ALT	ALTERNATE	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AMP	AMPLIFIER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AMT	AMOUNT	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ANL	ANNUNCIATOR	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AND	AND	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ANT	ANTENNA	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AP	ACCESS PANEL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
APC	ACOUSTICAL PANEL CEILING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
APPX	APPENDIX	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ARCH	ARCHITECT (URAL)	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ASE	ASBESTOS	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ASBL	ASBESTOS	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ASPH	ASPHALT	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
ASYM	ASYMMETRICAL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AV	AUDIO VISUAL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AVE	AVENUE	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AWC	ACOUSTICAL WALL COVERING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
AWP	ACOUSTICAL WALL PANEL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
B&B	BALLED AND BURLEPPED	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BAL	BALLET	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BB	BULLETIN BOARD	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BC	BOTTOM OF CURB	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BD	BOARD	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BEV	BEVEL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BF	BOTH SIDES	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BFF	BELOW FINISH FLOOR	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BFP	BACKFLOW PREVENTER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BTJLM	BUTIMINOUS	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BUT	BED JOINT	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BL	BASE LINE	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BLDG	BUILDING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BLK	BLOCK	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BLG	BLOCKING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BLKHD	BULKHEAD	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BLST	BALLAST	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BM	BEAM	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BO	BOTTOM OF	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BOC	BACK OF CURB	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BOV	BOTTOM OF WALL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRG	BRACING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRG JST	BRIDGING JOIST	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRG	BRIDGING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRG PL	BEARING PLATE	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRK	BRICK	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRK	BRICK	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRS	BRASS	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BRZ	BRAZING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BS	BOTH SIDES	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BSH	BASIN	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BTM	BOTTOM	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BUR	BUILT UP ROOF	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
BW	BOTH WAYS	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CIC	CENTER TO CENTER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CAC	CURB AND GUTTER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CAB	CABINET	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CAN	CATCH BASIN	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CCV	CLOSED CIRCUIT TELEVISION	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CER	CERAMIC	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CEN PLAS	CEMENT PLASTER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CER TILE	CERAMIC TILE	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CFB	COUNTER FLASHING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CFD	CORNER FLASHING	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHG	CHALKBOARD	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHANNEL	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHFR	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL
CHN	CHAMFER	DI	DIAMETER	HD	HEAVY DUTY	OFI	OWNER FURNISHED-OWNER INSTALLED	STL	STEEL

Plot Time Stamp: 5/16/2023 11:57:55 AM
File Location/Name: C:\1\Revit Projects\2022\508020-SWSWB-A22_vaughn.kelso@clarkensers.com.rvt

OCCUPANCY TYPE LEGEND

- Accessory Storage Areas, Mechanical Room
Business

CODE SYMBOL LEGEND

SYMBOL	DESCRIPTION	PROTECTION ELEMENTS
	CLEAR WIDTH	
	MAX EGRESS LOAD	
	ASSUMED EGRESS LOAD	
	EXIT - INTERIOR (assembly occ. over 50 and exits from floors)	
	FIRE EXTINGUISHER	SEE NOTE BELOW
	FIRE DEPARTMENT CONNECTION (FDC)	
	FIRE EXTINGUISHER SPACING (radius)	
	SMOKE BARRIER	1-hour resistive rated walls, 20-minute door assembly, Smoke dampers.
	1 HOUR FIRE BARRIER (occupancy & incidental use)	1-hour fire barrier wall construction, 1-hour rated door assembly for shaft, exit enclosure, & exit passageway wall, 45-min rated door assembly in other fire barriers, Fire dampers.
	FIRE PARTITION (dwelling / unit separations I-1 & R occupancies)	1-hour resistive rated walls, 45-minute rated door assembly, Fire dampers.
	ROOM DESIGNATION	Room type / Occupancy type Maximum Allowable Occupants
	Accumulated occupant loads for complex exit paths.	

FEC NOTE:
FIRE EXTINGUISHER CABINET IS NOTED AS FEC-1 BASIS OF DESIGN IS JL INDUSTRIES AMBASSADOR SERIES SURFACE MOUNTED FIRE EXTINGUISHER CABINET MOD. 1013 OR EQUIVALENT AND IS TO BE PROVIDED WITH JL INDUSTRIES COSMIC 10-E GENERAL PURPOSE FIRE EXTINGUISHER OR EQUIVALENT.

GENERAL INFORMATION	AGENCY INFORMATION: Nebraska Department of Transportation	AUTHORITY HAVING JURISDICTION: State of Nebraska, DAS
LOCATION: Ogallala, Nebraska Interstate 80 West Bound Rest Areas Mile Marker - 132	REASON FOR SUBMITTAL: New Building	
PROJECT DESCRIPTION A new interstate highway rest area with information lobby, staff office, rest rooms, and ancillary maintenance area for storage of lawnmowers and snow removal equipment.		
APPLICABLE CODES 2018 - International Building Code (IBC) 2018 - International Plumbing Code (IPC) 2018 - International Mechanical Code (IMC) 2018 - International Fire Code (IFC) 2020 - National Electric Code (NEC) Americans With Disabilities Act Accessibility Guidelines (ADAAG) American National Standards Institute (ANSI) 117.1 Guidelines for Accessible & Useable Buildings & Facilities	2010 - NFPA 110 - Standard for Emergency and Standby Power Systems 2009 - NFPA 90A - Installation of Air Conditioning and Ventilating Systems 2010 - NFPA 72 - National Fire Alarm Code 2009 - NFPA 54 - National Fuel Gas Code 2007 ASHRAE 90.1	
OCCUPANCY/STRUCTURAL CLASSIFICATION One story building with concrete, masonry and wood structure. Exterior walls will be masonry up to 110'-0" and metal panel with wood stud backup walls above 110'-0". Interior walls will be non load bearing on up to 110'-0" and wood stud and gypsum board above 110'-0". Floors will be slab on grade concrete. Roof structure will be wood truss.		
ACTIVE LIFE SAFETY SYSTEMS: Fire Alarm: Required/Provided: Not Required / Not Provided Per IBC 907.2.2 Smoke Detection: Required/Provided: Not Required / Not Provided Per IBC 907.2.2 Exit Signs: Required/Provided: Required / Battery Back-up Provided Emergency Lighting: Required/Provided: Required / Battery Back-up Provided Suppressor-Automatic: Required/Provided: Not Required / Not Provided Per IBC 903.2 & 903.2.9 Fire Extinguishers: Required/Provided: In Maintenance Area Only Per NFPA 10	PASSIVE LIFE SAFETY SYSTEMS: Corridor ratings: None Stairwells: None Shafts: None Occupancy Separations: None Fire Separations: None	

CODE ITEM			
OCCUPANCY CLASSIFICATION:	MIXED USE NON-SEPARATED B	TOTAL BUILDING SQUARE FOOTAGE:	
		LOWER LEVEL	NA
		FIRST FLOOR	2,300 SF
		SECOND FLOOR	NA
INCIDENTAL USE SEPARATIONS:	NA	PENTHOUSE	NA
BUILDING HEIGHT: (2018 IBC TABLE 504.4)		TOTAL	2,300 SF
ALLOWABLE	2 (40')	ROOF AREA	4,900 SF
ACTUAL	1 (20')		
RATIO OF PENTHOUSE AREA TO ROOF AREA	NA	EXIT ACCESS TRAVEL DISTANCE: (IBC 2018 TABLE 1017.2)	
		"B" OCCUPANCY	200 feet
		"S" OCCUPANCY	200 feet
BLDG. SQ. FT.: (2018 IBC TABLE 506.2)		COMMON PATH OF EGRESS TRAVEL (IBC 2018 TABLE 1006.2.1)	
ALLOWABLE PER FLOOR	9,500 sf	"B" OCCUPANCY	75 feet
MODIFIED PER SECTION 506	NA	"S" OCCUPANCY	75 feet
ACTUAL	2,300 sf	MAXIMUM DEAD-END CORRIDOR (IBC 2018 1020.4)	
		"B" OCCUPANCY	NA
FIRE RESISTIVE REQUIREMENTS: (2018 IBC TABLE 601)		EGRESS WIDTH: (IBC 2018 1006)	
STRUCTURAL FRAME	0	STAIRWAYS	NA
EXT. BEARING WALLS	0	OTHER COMPONENTS	0.2 inches per occupant
INT. BEARING WALLS	0		
EXT. NON-BEARING WALLS	0	INTERIOR WALL & CEILING FINISH (2018 IBC TABLE 803.13)	
INT. NON-BEARING WALLS	0	"B" OCCUPANCY	"S" OCCUPANCY
FLOORS	0	Exit Enclosures & Passageways	CLASS A NA
ROOFS	0	Corridors	CLASS B NA
		Rooms & Enclosed Spaces	CLASS C CLASS C
		ELEVATOR RECALL	
		FIRE SERVICE ACCESS ELEV.	Not Required / Not Provided
		OCCUPANT EVAC. ELEV.	Not Required / Not Provided
		ELEV. EMERGENCY SHUTDOWN	Not Required / Not Provided

OCCUPANCY KEY SCHEDULE - room		
OCCUPANCY	OCCUPANCY DESCRIPTION	FLOOR AREA PER OCCUPANT
B	Business	100 SF
S/ME	Accessory Storage Areas, Mechanical Room	300 SF

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A


May 15, 2023



Preliminary


Code Compliance Plan

G0.10




ADA - CHANGES IN LEVEL (303)

SCALE: 1/2" = 1'-0"




ADA - TURNING SPACE (304)

SCALE: 1/4" = 1'-0"




ADA - CLEAR FLOOR OR GROUND SPACE (305)

SCALE: 1/4" = 1'-0"




ADA - KNEE AND TOE CLEARANCE (306)

SCALE: 1/4" = 1'-0"




ADA - PROTRUDING OBJECTS (307)

SCALE: 1/4" = 1'-0"






ADA - REACH RANGES (308)

SCALE: 1/4" = 1'-0"




ADA - FIRE EXTINGUISHERS

SCALE: 3/8" = 1'-0"



MANEUVERING CLEARANCES AT MANUAL SWINGING DOORS AND GATES




MANEUVERING CLEARANCES AT DOORWAYS WITHOUT DOORS, SLIDING DOORS, GATES, AND FOLDING DOORS

MANEUVERING CLEARANCES AT RECESSED DOORS AND GATES


ADA - DOORS, DOORWAYS, AND GATES (404)

SCALE: 1/4" = 1'-0"




ADA - HANDRAILS (505)

SCALE: 3/8" = 1'-0"




ADA - WALKING SURFACES (403)

SCALE: 1/4" = 1'-0"




ADA - BENCHES (903)

SCALE: 3/8" = 1'-0"




ADA - RAMPS (405)

SCALE: 1/4" = 1'-0"




ADA - STAIR NOSINGS (504)

SCALE: 1/2" = 1'-0"




ADA - HANDRAIL PROFILES (505)

SCALE: 3/8" = 1'-0"



ADA - ELEVATORS (407)

SCALE: 3/4" = 1'-0"



ADA - SIGNAGE MOUNTING (703)

SCALE: 3/8" = 1'-0"

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area
Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

ADA Details


G0.20

Plot Time Stamp: 5/16/2023 11:57:59 AM
File Location/Name: C:\1\Revit Projects\2022\508020-SWSWB-A22_vaughn.kelso@clarkensers.com.rvt







ADA - WATER CLOSETS AND TOILET COMPARTMENTS (604)

SCALE: 1/4" = 1'-0"





ADA - URINALS (605)

SCALE: 1/4" = 1'-0"




WATER CLOSETS SERVING CHILDREN (604.9)

SCALE: 3/8" = 1'-0"



ADA - SHOWER SEATS (610)

SCALE: 3/8" = 1'-0"



ADA - WATER COOLER & BOTTLE FILLERS (602)

SCALE: 1/4" = 1'-0"

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary


ADA Details

G0.21



WOOD STUD FURRING - (TYPE A, B, C, D)


TAG	SUPPORT	FACING - TAG SIDE	FACING - OPP SIDE	ACTUAL SIZE	HEIGHT	RATING	STC	INSULATION	REMARKS
D4	2x4 WOOD STUDS @ 16" O.C.	(1) LAYER BRUSHED TEXTURE 22ga. 304 STAINLESS STEEL PANEL OVER 5/8" PLYND.	-	4 1/4"	ENTIRE ASSEMBLY TO STRUCTURAL DECK	NA	NA	-	



WOOD STUD PARTITION - (TYPE F, G, H, J, K)

NOTE: FOR STUD GAUGE SEE INTERIOR STEEL STUD FRAMING GAUGE TABLE TYPE 1, THIS SHEET

TAG	SUPPORT	FACING - TAG SIDE	FACING - OPP SIDE	ACTUAL SIZE	HEIGHT	RATING	STC	INSULATION	REMARKS
F3	2x4 WOOD STUDS @ 16" O.C.	(1) LAYER 5/8" TYPE 'X' GPDW, PT.	(1) LAYER 5/8" TYPE 'X' GPDW, PT.	4 7/8"	STUDS TO STRUCTURE AND GPDW TO MIN. 6" ABOVE CEILING	NA	NA		



MASONRY PARTITION - (TYPE S, T, U)

*FIRE RATED CONSTRUCTION NOTE: PROVIDE MATERIALS AND CONSTRUCTION IDENTICAL TO THOSE OF ASSEMBLIES WITH FIRE-RESISTANCE RATINGS DETERMINED PER ASTM E 119 BY A TESTING AND INSPECTING AGENCY.

TAG	SUPPORT	FACING - TAG SIDE	FACING - OPP SIDE	ACTUAL SIZE	HEIGHT	RATING	STC	INSULATION	REMARKS
S6	6" CMU	SEE ROOM FINISH SCHEDULE.	SEE ROOM FINISH SCHEDULE.	5 5/8"	TO 7'-4" A.F.F.	NA	NA	-	
S8	8" CMU	SEE ROOM FINISH SCHEDULE.	SEE ROOM FINISH SCHEDULE.	7 5/8"	TO 10'-0" A.F.F.	NA	NA	-	
S10	10" CMU	SEE ROOM FINISH SCHEDULE.	SEE ROOM FINISH SCHEDULE.	9 5/8"	TO 10'-0" A.F.F.	NA	NA	-	

1 WALL TYPES

SCALE: 1 1/2" = 1'-0"

GENERAL NOTES:

- 1) CONTRACTOR TO COORDINATE SPACING OF STUDS W/ MECH. AND ELECTRICAL DRAWINGS.
- 2) WHERE PLYWOOD IS INDICATED ON THE DRAWINGS CONTRACTOR SHALL INSTALL PLYWOOD IN LIEU OF GPDW INDICATED. SEE ELECTRICAL AND ARCHITECTURAL SHEETS FOR PLYWOOD LOCATIONS.
- 3) STC-RATED ASSEMBLIES AND PARTITIONS INDICATED TO RECEIVE SOUND INSULATION: SEAL CONSTRUCTION AT PERIMETERS, BEHIND CONTROL JOINTS AND AT OPENINGS & PENETRATIONS WITH A CONTINUOUS BEAD OF ACOUSTICAL JOINT SEALANT. INSTALL ACOUSTICAL JOINT SEALANTS AT BOTH FACES OF PARTITIONS, AT PERIMETER AND THROUGH PENETRATIONS.
- 4) ALL WALL FRAMING THAT DOES NOT EXTEND TO STRUCTURE OR DECK SHALL BE BRACED AT 48" O.C. MIN.
- 5) PAINT WALLS PER ROOM FINISH SCHEDULE.
- 6) ALL WALL BOARD IN MECHANICAL ROOMS SHALL BE MOLD & MOISTURE RESISTANT DRYWALL.



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A


May 15, 2023



Preliminary

Wall Type Schedule &
Details

A0.00



1 **FIRST FLOOR PLAN**
SCALE: 1/4" = 1'-0"

GENERAL PLAN NOTES

1. ALL WALL / GENERAL PLAN DIMENSIONS ARE TO FACE OF MASONRY, FACE OF CONCRETE, AND TO FACE OF GYP. BOARD, TYP.
2. SEE SHEET A1.12 FOR CONTROL JOINT PLAN.
3. CONSTRUCTION OF WALLS ARE DESIGNATED STARTING ON TAG SIDE OF WALL.
4. REFER TO STRUCTURAL DRAWINGS FOR GROUTING AND REINFORCEMENT OF CMU WALLS.
5. ALL INTERIOR WALL FRAMING NOTED IN WALL TYPE SCHEDULE EXTENDS TO STRUCTURAL DECKING, BRACE AS REQUIRED.
6. PROVIDE BULLNOSE UNITS @ ALL DOOR AND WINDOW OPENINGS, END WALLS, AND OUTSIDE CORNERS IN CMU WALLS.
7. REFER TO CODE COMPLIANCE PLANS FOR LOCATION OF FIRE RATED WALLS AND SMOKE SEPARATION WALL LOCATIONS AND REQUIREMENTS.
8. ALL OPENINGS IN RATED ASSEMBLIES SHALL BE SEALED WITH FIRE / SMOKE RATED MATERIALS AND ASSEMBLIES. INSTALL RATED JOINT SEALANTS AT BOTH FACES OF PARTITIONS, AT PERIMETERS, AND THROUGH FIRE RATED ASSEMBLIES. REFERENCE CODE COMPLIANCE PLANS FOR LOCATION OF RATED ASSEMBLIES.
9. ALL EXPANSION JOINT COVERS WITH CONNECTION TO RATED ASSEMBLIES SHALL MEET THE SAME REQUIRED RATING AS THE ASSEMBLY. REFERENCE CODE COMPLIANCE PLANS FOR LOCATION OF RATED ASSEMBLIES.
10. ALL STC-RATED WALL ASSEMBLIES AND PARTITIONS INDICATED SHALL HAVE STAGGERED SHEATHING AND GYP. BOARD JOINTS ON OPPOSITE SIDES OF ASSEMBLIES. REFERENCE WALL TYPE SCHEDULE FOR SOUND ATTENUATION INSULATION REQUIRED WITHIN STUD CAVITIES. SEAL ASSEMBLIES AT CONSTRUCTION PERIMETERS, DECKING MATERIAL (TOP & BOTTOM), BEHIND CONTROL JOINTS, AND AT ALL OPENINGS AND PENETRATIONS WITH A CONTINUOUS BEAD OF ACOUSTICAL JOINT SEALANT. INSTALL ACOUSTICAL JOINT SEALANTS AT BOTH FACES OF ASSEMBLIES.
11. GENERAL CONTRACTOR SHALL COORDINATE REPAINTING OF WALLS BETWEEN SUBCONTRACTORS AFTER EXISTING FIXTURES ARE SCHEDULED TO BE REMOVED AND PRIOR TO FIXTURES BEING REINSTALLED. REFER TO ELECTRICAL & MECHANICAL PLANS.
12. ALL WALL BOARD IN MECHANICAL ROOMS SHALL BE MOLD & MOISTURE RESISTANT DRYWALL.
13. REFERENCE REFLECTED CEILING PLAN FOR ADDITIONAL WALL TAGS ABOVE 11'0" - 0".


SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

First Floor Plan

A1.11

Plot Time Stamp: 5/16/2023 11:57:05 AM
File Location/Name: C:\11 Revit Projects\2022\508020-SWSWB-A22_vaultin.kiso@clarkensons.com.rvt




1



CONCRETE FLOOR SLAB CONTROL JOINT PLAN

SCALE: 1/4" = 1'-0"



SHEET HISTORY:

ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Concrete Floor Slab
Control Joint Plan

A1.12

Plot Time Stamp: 5/16/2023 11:57:07 AM
File Location/Name: C:\1\Revit Projects\2022\508020-SWSWB-A22_vaughn.kelso@clarkensers.com.rvt



REFLECTED CLG GENERAL NOTES:

1. LIGHTING FIXTURES AND MECHANICAL DIFFUSERS / GRILLES ARE SHOWN FOR REFERENCE ONLY. SEE ELECTRICAL AND MECHANICAL DRAWINGS FOR EXACT LOCATIONS
2. ELEVATION TAGS ARE IN REFERENCE TO ARCHITECTURAL ELEVATIONS
3. SEE FINISH SHEETS FOR PAINT.
4. PROVIDE ACCESS PANELS AS REQUIRED IN HARD LID CEILINGS. COORDINATE WITH MECHANICAL AND ELECTRICAL CONTRACTORS.

REFLECTED CLG LEGEND

	5/8" SUSPENDED GPDW CEILING SYSTEM
	SUSPENDED P.C. PLASTER SOFFIT SMOOTH FINISH
	2x2 ACCESS PANEL, REF. SPEC.
	RECESSED & PENDANT MOUNTED LIGHT FIXTURES, REF. ELECTRICAL
	RECESSED DOWNLIGHT, REF. ELECTRICAL
	EXIT SIGNAGE, REF. ELECTRICAL
	RETURN AIR / EXHAUST AIR GRILLE, REF. MECHANICAL
	SUPPLY AIR DIFFUSER, REF. MECHANICAL

RCP ABBREVIATIONS

APC - ACOUSTICAL PANEL CEILING
LWG - LINEAR WOOD CEILING
MPS - METAL PANEL SOFFIT
GPDW - GYPSUM DRY WALL

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary

First Floor Reflected Ceiling Plan

A1.21



ROOF PLAN GENERAL NOTES:

1. ALL ROOFING SHALL BE INSTALLED IN ACCORDANCE WITH - THE NRCA ROOFING MANUAL: METAL PANEL AND SPF ROOF SYSTEMS - 2016.
2. ROOFING SYSTEM SHALL BE A MINIMUM 22ga. DEEP RIBBED STANDING SEAM MECHANICALLY FASTENED. ROOFING SYSTEM OVER SELF-ADHERING MEMBRANE UNDERLAYMENT OR AS PER MANUFACTURER'S REQUIREMENTS. SYSTEM SHOULD QUALIFY FOR A MINIMUM 20 YEAR WARRANTY. COLOR TO MATCH CLEAR SATIN ANODIZED FRAMING SYSTEM.
3. THE ROOF SLOPE SHALL BE 4" PER FOOT. UNLESS INDICATED OTHERWISE. SLOPE DIRECTION IS DOWN AS INDICATED. SLOPE IS NOTED IN DISTANCE PER FOOT.
4. PROVIDE CHAMFERS, CRICKETS, BOOTS AND / OR SADDLES AS REQUIRED AT OBSTRUCTIONS TO DRAINAGE.
5. VERIFY ALL MECHANICAL PENETRATIONS WITH MECHANICAL. AND MECHANICAL CONTRACTOR.
6. INSTALL GUTTERS AND DOWNSPOUTS IN ACCORDANCE WITH NRCA ROOFING MANUAL. INSTALL NEW ACCESSORIES AS REQUIRED PER ORIGINAL MANUFACTURER.
7. INSTALL GUTTERS AND DOWNSPOUTS IN ACCORDANCE WITH SHEET METAL AND AIR CONDITIONING CONTRACTORS NATIONAL ASSOCIATION (SMACNA) AND NATIONAL ROOFING CONTRACTORS ASSOCIATION (NRCA) ROOFING MANUAL.



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A


May 15, 2023




Preliminary

Roof Plan

A1.30



1 WEST ELEVATION
SCALE: 1/4" = 1'-0"



2 NORTH ELEVATION
SCALE: 1/4" = 1'-0"

EXTERIOR MATERIALS KEY	
	BRICK ENDICOTT - 2 1/4" MERIDIAN - 1/3 RUNNING BOND - REF. SPEC FOR BLEND
	BURNISHED CMU COUNTY MATERIALS - COLOR TBD - BLEND OF NOM. 8" & 4" TALL UNITS w/ SCORING - REF. DETAIL 3, SHEET A2.10
	PLASTER WHITE FOR CEILING APPLICATION, SW 7020 BLACK FOX FOR WALL APPLICATION
	CAST STONE SEE SPEC.
	METAL ROOF STANDING SEAM METAL ROOFING PANELS. SEE SPEC.
	FORMED METAL PANEL PRE-FINISHED FORMED METAL WALL PANELS. SEE SPEC.

NOTE: MATERIALS LISTED ARE BASIS OF DESIGN. REFER SPEC. FOR APPROVED ALTERNATES

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

West and North Exterior Elevations

A2.11



1 BUILDING CROSS SECTION NORTH TO SOUTH LOOKING WEST
SCALE: 1/4" = 1'-0"



2 BUILDING CROSS SECTION EAST TO WEST LOOKING NORTH
SCALE: 1/4" = 1'-0"

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023








Preliminary

Building Cross Sections

A3.10

Plot Time Stamp: 5/16/2023 11:57:22 AM
File Location/Name: C:\Users\jensen\OneDrive\Projects\2022\508020-SWSWB-A42_vault\h.kelso\dwg\A4.10_Prelim.dwg



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023






Preliminary

Wall Sections

A4.10

Plot Time Stamp: 5/16/2023 11:57:24 AM
File Location/Name: C:\1\ Revit Projects\2022\508020-SWSWB-A22_vaughn.kelso@clarkensers.com.rvt



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A


May 15, 2023




Preliminary

Wall Sections


A4.11




1 NORTH WALL ROOM 107
SCALE: 1/4" = 1'-0"



4 SOUTH WALL ROOM 102
SCALE: 1/4" = 1'-0"



8 SOUTH WALL ROOM 101
SCALE: 1/4" = 1'-0"




13 SOUTH WALL ROOM 100
SCALE: 1/4" = 1'-0"

14 WEST WALL ROOM 100
SCALE: 1/4" = 1'-0"


2 SOUTH WALL ROOM 107
SCALE: 1/4" = 1'-0"



5 SOUTH WALL ROOM 104
SCALE: 1/4" = 1'-0"



10 SOUTH WALL @ VENDING
SCALE: 1/4" = 1'-0"



11 WEST WALL @ VENDING
SCALE: 1/4" = 1'-0"


TOILET ACCESSORY SCHEDULE						
ASBR	ACCESSORY	MANUFACTURER	MODEL NUMBER	FURNISHED BY	INSTALLED BY	REMARKS
GB-1	36" GRAB BAR	BOBBICK	B-8806 99X36	CONTRACTOR	CONTRACTOR	
GB-2	48" GRAB BAR	BOBBICK	B-8806 99X48	CONTRACTOR	CONTRACTOR	
GB-3	18" GRAB BAR - VERTICAL	BOBBICK	B-8806 99X18	CONTRACTOR	CONTRACTOR	
HD-1	HAND DRYER	WORLD DRYER, INC.	SLIMDRI L-973	CONTRACTOR	CONTRACTOR	ADA DEPTH
MR-1	2-6" W x 4-6" H MIRROR	BOBBICK	B-2908	CONTRACTOR	CONTRACTOR	
SNV-1	SANITARY NAPKIN DISPOSAL	BOBBICK	B-254	CONTRACTOR	CONTRACTOR	
SNV-1	SANITARY NAPKIN VENDOR	BOBBICK	B-37663 25	CONTRACTOR	CONTRACTOR	RECESSED
SNV-2	SANITARY NAPKIN VENDOR	BOBBICK	B-3766 25	CONTRACTOR	CONTRACTOR	SEMI-RECESSED
TTD-1	TOILET TISSUE DISPENSER	BOBBICK	B-2888	CONTRACTOR	CONTRACTOR	

15 NORTH WALL ROOM 100
SCALE: 1/4" = 1'-0"


RESTROOM GENERAL NOTES:

- TOILET PARTITION DOORS: 20 GA \"LEATHER\" TEXTURE STAINLESS STEEL DOOR WITH PLYWOOD CORE, CONTINUOUS STAINLESS STEEL HINGE, FLAT STRIKE, OCCUPANCY INDICATOR, AND MOUNT BOTTOM OF DOOR AT 12\"/>


3 TYP. HAND DRYER
SCALE: 1/4" = 1'-0"



7 NORTH WALL ROOM 104
SCALE: 1/4" = 1'-0"



12 NORTH WALL @ VENDING
SCALE: 1/4" = 1'-0"



15 NORTH WALL ROOM 100
SCALE: 1/4" = 1'-0"

FIXTURE SCHEDULE

DESCRIPTION	TYPE	MOUNTING LOCATION
WATER COOLER	STANDARD	38'-43\"/>

*TO COMPLY WITH 2010 ADA STANDARDS OF ACCESSIBLE DESIGN AND MFR. RECOMMENDATIONS.

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area
Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary


Enlarged Interior/Exterior
Elevations & Schedule

A6.10



ALUMINUM FRAME TYPE

SCALE: 1/4" = 1'-0"




ALUMINUM DOOR TYPES

SCALE: 1/4" = 1'-0"


OVERHEAD COILING DOOR TYPE

SCALE: 1/4" = 1'-0"



HOLLOW METAL DOOR TYPES

SCALE: 1/4" = 1'-0"



HOLLOW METAL FRAME TYPES

SCALE: 1/4" = 1'-0"

DOOR NO.	DOOR WIDTH	DOOR HEIGHT	DOOR			FRAME			FIRE RATING	ADA OPERATOR	CARD READER	DELAYED EGRESS	HOLD OPEN	MAGNETIC LOCK	SOUND SEALS	HARDWARE	REMARKS
			WIDTH	HEIGHT	TYPE	FINISH	TYPE	FINISH									
100	6'-0"	3'-0"	8'-0"	ALD-1	HMD-1	HPC-2	HMF-1	HPC-2									
101A	3'-0"	7'-10"	HMD-1	HPC-2	HMF-1	HPC-2											
101B	5'-6"	4'-4"	OD-1	PREFIN		PREFIN											
102	5'-4"	9'-7 1/2"	HMD-2	HPC-2	HMF-3	HPC-2											
103	3'-0"	7'-0"	HMD-1	HPC-2	HMF-2	HPC-2											
104	3'-0"	7'-10"	HMD-1	HPC-2	HMF-1	HPC-2											
105A	3'-0"	7'-10"	HMD-1	HPC-2	HMF-1	HPC-2											
105B	6'-0"	3'-0"	ALD-2	PREFIN	ALF-1	PREFIN											
106	3'-0"	7'-10"	HMD-1	HPC-2	HMF-1	HPC-2											
107	5'-4"	9'-7 1/2"	HMD-2	HPC-2	HMF-3	HPC-2											

DOOR SCHEDULE REMARKS	
NO.	DOOR REMARKS
1	JAMB MOUNTED
2	SMOKE SEAL
3	CONTINUOUS HINGE

DOOR & FRAME TYPE GENERAL NOTES

1. PROVIDE SAFETY GLAZING OR FIRE-PROTECTION-RATED GLAZING IN LOCATIONS REQUIRED BY CURRENT LOCAL CODE. NOTIFY ARCHITECT OF CHANGES REQUIRED TO THE DRAWINGS. PROVIDE OBSCURE GLAZING AS INDICATED.
2. PROVIDE AND INSTALL SAFETY GLAZING IN LOCATIONS AS PER SECTION 2406 & 2408 OF THE 2019 INTERNATIONAL BUILDING CODE.
3. ALL DIMENSIONS ARE NOMINAL. ACTUAL DIMENSIONS TO BE PROVIDED BY SUPPLIER W/ ADJUSTMENTS MADE FOR INSTALLATION TOLERANCES REQUIRED. VERIFY ALL EXISTING OPENINGS PRIOR TO ORDER OF ALL NEW DOORS, DOOR FRAMES AND WINDOW FRAMES.
4. SEE FLOOR PLANS FOR DIRECTION OF DOOR SWINGS.
5. REFER TO WALL TYPE THICKNESS FOR THROAT DEPTHS OF HOLLOW METAL DOOR AND WINDOW FRAMES INSTALLED IN STEEL STUD WALLS W/ GYPSUM. HOLLOW METAL DOOR AND WINDOW FRAMES INSTALLED IN PRECAST, CAST-IN PLACE OR C.M.U. WALLS SHALL HAVE A STANDARD 6" NOMINAL THROAT DEPTH AND SHALL BE CENTERED IN THE WALL, UNLESS NOTED OTHERWISE.
6. ALL INTERIOR HOLLOW METAL DOOR FRAMES SHALL BE FILLED FULL W/ BATT INSUL. COORDINATE WITH ELECTRICAL TRADES, FINISH HARDWARE AND ELECTRONIC EQUIPMENT.
7. ALL EXTERIOR ALUMINUM WINDOW FRAMING HAVE 1" INSULATED LOW 'E' GLAZING.
8. ALL INTERIOR DOOR FRAMES OF C.M.U. WALLS BEGIN 4" FROM THE FINISH FACE OF THE ADJACENT WALLS, AND ALL INTERIOR DOOR FRAMES OF STUD WALLS W/ GYPSUM WALLS BEGIN 4" FROM THE FINISH FACE OF THE ADJACENT WALLS UNLESS OTHERWISE NOTED.
9. CURTAIN WALL WINDLOADS AND DEADLOADS ENGINEERED BY WINDOW SUPPLIER. WINDLOAD ANCHORS SUPPLIED BY WINDOW SUPPLIER. DEADLOADS TO TRANSFER TO FOUNDATION. SEE STRUCTURAL DRAWINGS FOR WINDLOAD AND DEADLOAD REQUIREMENTS. PROVIDE EXPANSION MULLIONS IN LONGER FRAMES AS REQUIRED.
10. HOLLOW METAL DOOR & FRAME FINISH SHALL BE A HIGH PERFORMANCE COATING (HPC) TO MATCH CLEAR ANODIZED ALUMINUM FRAMING.
11. MULLION LOCATIONS SHALL BE AS INDICATED ON THE DRAWINGS AND SHALL BE REFLECTED IN THE SHOP DRAWINGS. NOTIFY ARCHITECT OF ANY CHANGES OR DEVIATIONS.
12. BORROWED LIGHT LOCATIONS SHALL BE AS INDICATED ON THE PLAN DRAWINGS AND SHALL BE REFLECTED IN THE SHOP DRAWINGS. NOTIFY ARCHITECT OF ANY CHANGES OR DEVIATIONS.

PROVIDE GLAZING PANELS AS INDICATED.

- (A) INDICATES 1" INSULATED ALUMINUM PANEL.
- (IG) INDICATES 1" CLEAR INSULATING VISION GLASS.
- (TIG) INDICATES 1" CLEAR INSULATING TEMPERED GLASS.
- (TR) INDICATES A TRANSLUCENT INSULATING GLASS.



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary


Door Schedule, Door Types, Frame Types & Casework Sections

A6.40




1 SECTION

SCALE: 3/4" = 1'-0"




2 SECTION

SCALE: 3/4" = 1'-0"




3 SECTION

SCALE: 3/4" = 1'-0"




4 SECTION

SCALE: 3/4" = 1'-0"




5 SECTION

SCALE: 3/4" = 1'-0"




6 SECTION


SCALE: 3/4" = 1'-0"




1 PLAN DETAIL
SCALE: 1 1/2" = 1'-0"




2 PLAN DETAIL
SCALE: 1 1/2" = 1'-0"




3 PLAN DETAIL
SCALE: 1 1/2" = 1'-0"




4 PLAN DETAIL
SCALE: 1 1/2" = 1'-0"




5 SECTION DETAIL
SCALE: 3" = 1'-0"




10 SECTION DETAIL
SCALE: 1 1/2" = 1'-0"




11 SECTION DETAIL
SCALE: 1 1/2" = 1'-0"



12 SECTION DETAIL
SCALE: 1 1/2" = 1'-0"



13 SECTION DETAIL
SCALE: 1 1/2" = 1'-0"



9 SECTION DETAIL
SCALE: 3" = 1'-0"

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Plan and Section Details

A7.10

- GENERAL NOTES:
1. ALL WORK SHALL CONFORM TO ALL CHAPTERS OF TITLE 124 - RULES AND REGULATIONS FOR THE DESIGN, OPERATION AND MAINTENANCE OF ON-SITE WASTEWATER TREATMENT SYSTEMS MINIMUM DOSING VOLUME IS 420 GALLONS AND THE MAXIMUM IS 1,500 GALLONS.
 2. DESIGN DATA:
10,000 GPD
15 MIN/INCH PERCOLATION RATE UTILIZING SANDY LOAM LINER




CONTRACTOR SHALL EXERCISE EVERY PRECAUTION TO PREVENT DAMAGE TO ANY PUBLIC OR PRIVATE UTILITY LINE OR APPURTENANCE AND SHALL BE LIABLE FOR ANY DAMAGE INCURRED AS A RESULT OF MISOPERATIONS. ALL UTILITIES SHALL BE MARKED BY THE FIELD PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING ALL UTILITIES. SERVICE CONNECTIONS ARE NOT SHOWN EXCEPT AS NOTED. EXISTING UTILITIES SIZES AND LOCATION BOTH HORIZONTAL AND VERTICAL ARE APPROXIMATE AND SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION BY THE CONTRACTOR.

CONSTRUCTION DOCUMENT


Sidney West Bound Rest Area

Sidney, Nebraska

TCEP No.: 508-015-17
NDOT No.: NH-80-2(92)
Control No.: 51276A




Sanitary Sewer
Plan & Profiles
C1.01A



Potable Water Plan & Profiles **C3.01A**


ABBREVIATIONS		LIGHTING		ELECTRICAL DISTRIBUTION		ELECTRICAL DISTRIBUTION EQUIPMENT		MOTOR CONTROL & MOTOR CONTROL EQUIPMENT		SPECIAL SYSTEMS	
AF	ABOVE FINISHED FLOOR		POLE MOUNTED EXTERIOR LIGHT FIXTURE. LETTER INDICATES FIXTURE AND FUSE TYPE.	S	SINGLE POLE SWITCH		LIGHTING AND APPLIANCE PANEL		MOTOR - HORSEPOWER AS INDICATED ON DRAWINGS		CLOCK AND CLOCK HANGER OUTLET
FG	ABOVE FINISH GRADE		2 X 4 TROFFER RECESSED IN GYRO. GWBO OR PLASTER CEILING. LETTER NUMBER DENOTES FIXTURE TYPE.	S ₃	THREE WAY SWITCH		LIGHTING RELAY PANEL		NON-FUSED DISCONNECT SWITCH. ASSUME 30A/3P UNLESS OTHERWISE NOTED.		ELAPSED TIME INDICATOR CLOCK
CTV	CABLE TELEVISION		2 X 4 TROFFER RECESSED IN GYRO. GWBO OR PLASTER CEILING, WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	S _D	DIMMER SWITCH		MOTOR CONTROL CENTER OR SWITCHBOARD		FUSED DISCONNECT SWITCH. FUSE SIZE AS NOTED ON DRAWINGS. ASSUME 30A/3P UNLESS OTHERWISE NOTED.		CLOCK MASTER CONTROL
CE	CLOSED CIRCUIT TELEVISION		1 X 4 TROFFER RECESSED IN GYRO. GWBO OR PLASTER CEILING, WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	S _{MC}	MOMENTARY CONTACT SWITCH		POWER PANEL (DISTRIBUTION)		COMBINATION FMR MAGNETIC MOTOR STARTER WITH HOK SELECTOR SWITCH AND NON-FUSED DISCONNECT SWITCH. ASSUME NEMA SIZE 1 STARTER AND 30A/3P SWITCH UNLESS OTHERWISE NOTED.		CLOCK SYSTEM SIGNAL GENERATOR
(ER)	SUBSCRIPT (ER) ADJACENT TO ANY DEVICE INDICATES EXISTING TO BE RELOCATED.		1 X 4 TROFFER RECESSED IN GYRO. GWBO OR PLASTER CEILING. LETTER NUMBER DENOTES FIXTURE TYPE.	S _{TE}	THERMAL ELEMENT SWITCH		TRANSFORMER		COMBINATION FMR MAGNETIC MOTOR STARTER WITH HOK SELECTOR SWITCH AND NON-FUSED DISCONNECT SWITCH. ASSUME NEMA SIZE 1 STARTER AND 30A/3P SWITCH UNLESS OTHERWISE NOTED.		CCTV CAMERA
EW	ELECTRIC WATER COOLER		1 X 4 TROFFER RECESSED IN GYRO. GWBO OR PLASTER CEILING. LETTER NUMBER DENOTES FIXTURE TYPE.	S _O	OCCUPANCY SENSING SWITCH (SEE SPECIFICATION)		CIRCUIT BREAKER		COMBINATION MOTOR STARTER/DISCONNECT PROVIDED BY OTHERS.		CCTV CAMERA OUTLET
F	SUBSCRIPT F ADJACENT TO ANY DEVICE INDICATES FLOOR		1 X 4 TROFFER RECESSED IN GYRO. GWBO OR PLASTER CEILING, WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	Φ	20A, 125V DOUBLE DUPLEX CONVENIENCE OUTLET (NEMA 5 - 20P)		FUSIBLE SWITCH		COMBINATION FMR MAGNETIC MOTOR STARTER WITH HOK SELECTOR SWITCH AND FUSED DISCONNECT SWITCH. ASSUME NEMA SIZE 1 STARTER AND 30A/3P SWITCH UNLESS OTHERWISE NOTED.		CCTV MONITOR AND OUTLET
GI	GROUND FAULT INTERRUPTER		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	Φ	20A, 125V DUPLEX CONVENIENCE OUTLET (NEMA 5 - 20R)		AUTOMATIC TRANSFER SWITCH		COMBINATION FMR MAGNETIC MOTOR STARTER WITH HOK SELECTOR SWITCH AND FUSED DISCONNECT SWITCH. ASSUME NEMA SIZE 1 STARTER AND 30A/3P SWITCH UNLESS OTHERWISE NOTED.		VIDEO CONFERENCING OUTLET
H	SUBSCRIPT H DENOTES HOSPITAL GRADE		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	Φ	20A, 125V DUPLEX CONVENIENCE OUTLET (NEMA 5 - 20R)		POTENTIAL TRANSFORMER		COMBINATION FMR MAGNETIC MOTOR STARTER WITH HOK SELECTOR SWITCH. ASSUME NEMA SIZE 1 STARTER UNLESS OTHERWISE NOTED.		CCTV MONITOR OUTLET
HA	HAND-OFF-AUTO		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	Φ	20A, 125V DUPLEX CONVENIENCE OUTLET ON EMERGENCY SYSTEM (NEMA 5 - 20R)		CURRENT TRANSFORMER		COMBINATION FMR MAGNETIC MOTOR STARTER WITH HOK SELECTOR SWITCH. ASSUME NEMA SIZE 1 STARTER UNLESS OTHERWISE NOTED.		2 GANG TV OUTLET BOX WITH SINGLE GANG EXTENSION RING FLUSH MOUNTED AT 8' AFF UNLESS OTHERWISE NOTED.
NE	NON-FUSED		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	Φ	20A, 125V DUPLEX CONVENIENCE OUTLET - CEILING AND FLOOR MOUNTED (NEMA 5 - 20R)		GROUND		START/STOP PUSH BUTTON		INTERCOM ADDRESS SPEAKER - SURFACE MOUNTED
NC	NOT IN CONTRACT		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE.	Φ	SPECIAL PURPOSE OUTLET - TYPE AS NOTED ON DRAWINGS		ENGINE GENERATOR		3 POSITION PUSH BUTTON		INTERCOM ADDRESS SPEAKER - WALL MOUNTED
OHE	OVERHEAD ELECTRICAL		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE. REFER TO DRAWINGS FOR FIXTURE MOUNTING HEIGHT.	Φ	PICGAL DENOTES CONNECTION TO EQUIPMENT		REMOTE GENERATOR ANNUNCIATOR		PUSH BUTTON		PUBLIC ADDRESS TRUMPET
OH	OVERHEAD TELEPHONE		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE. REFER TO DRAWINGS FOR FIXTURE MOUNTING HEIGHT.	Φ	JUNCTION BOX - CEILING, FLOOR, AND WALL MOUNTING		METER				VOLUME CONTROL FOR SPEAKER
PVC	POLYVINYL CHLORIDE		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE. REFER TO DRAWINGS FOR FIXTURE MOUNTING HEIGHT.	Φ	FLOOR BOX		PANELBOARD TAG. SEE THE CORRESPONDING PANELBOARD SCHEDULE AND/OR ONE LINE DIAGRAM FOR ADDITIONAL INFORMATION.				SOUND DISTRIBUTION RACK
RG	RIGID GALVANIZED STEEL		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE. REFER TO DRAWINGS FOR FIXTURE MOUNTING HEIGHT.	Φ	2 GANG TELECOMMUNICATIONS OUTLET BOX WITH SINGLE GANG EXTENSION RING FLUSH MOUNTED AT 18" AFF UNLESS OTHERWISE NOTED. ROUTE IN 1" CONDUIT FROM BOX AND STUB INTO THE MAINTENANCE ROOM.		FIRE ALARM				MICROPHONE
RS	TAMPER RESISTANT		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE. REFER TO DRAWINGS FOR FIXTURE MOUNTING HEIGHT.	Φ	TELEPHONE TERMINAL BOARD OR TERMINAL CABINET - SIZE AND TYPE AS INDICATED (TBS OR TTD)		SMOKE DETECTOR				SECURITY SYSTEM CARD READER AND OUTLET BOX
UGE	UNDERGROUND ELECTRICAL		2 X 2 TROFFER WITH EMERGENCY BATTERY BACK-UP AND/OR ON EMERGENCY/NIGHT LIGHTING CIRCUIT. LETTER NUMBER DENOTES FIXTURE TYPE. REFER TO DRAWINGS FOR FIXTURE MOUNTING HEIGHT.	Φ	BRANCH CIRCUIT HOMERUN TO PANEL (NUMBER OF ARROWS INDICATES NUMBER OF CIRCUITS. NUMBER OF TICK MARKS INDICATES NUMBER OF WIRES). NUMBER 12AWG. MINIMUM UNLESS OTHERWISE NOTED. IF TICK MARKS ARE SHOWN, NUMBER 12 AWG IN 1/2" CONDUIT.						




GENERAL LIGHTING NOTES:

- GENERAL POWER & AUXILIARY SYSTEMS NOTES:

- | LIGHTING FIXTURE SCHEDULE | | | | | | | | |
|---------------------------|---------------|---|-------------------------------|-----------|------|----------------|--------------|--|
| Fixture Type | Manufacturers | Catalog Numbers | Description | Lamp Type | Volt | VA | Mounting | Remarks |
| A | MARK LIGHTING | SL4L-LQP-4FT/9FT/110FT/20FT-FLP-WFL-80CRI-35K-400LM-NODIM-120-BAA | RECESSED LINEAR FIXTURE | LED | 120 | 16,24,32,40,80 | RECESSED | PROVIDE FIXTURES IN LENGTHS INDICATED ON THE PLANS. SEE THE ARCHITECTURAL SHEETS FOR CEILING MOUNTING DETAILS. PROVIDE EMERGENCY BACKUP FOR FIXTURE TYPE 'A1'. |
| B | MARK LIGHTING | S4LWID-LIP-6FT/12FT/20FT-MSL8/MSL6/MSL5-80CRI-35K-400LM-IB80CRI-35K-400LM-F-NODIM-120-WHT-BAA | WALL MOUNT LINEAR FIXTURE | LED | 120 | 32,48,80 | SURFACE | SURFACE MOUNT FIXTURE AT 9'-0" AFF. PROVIDE FIXTURES IN LENGTHS SHOWN ON THE PLANS. PROVIDE FIXTURE, TYPE 'B1' WITH EMERGENCY DRIVER. |
| C | LITHONIA | BLWP4-30L-ADP-MVOLT-E21-LP835-BAA | 4" INDUSTRIAL FIXTURE | LED | UNV | 25 | PENDANT | PENDANT MOUNT FIXTURE AS HIGH AS POSSIBLE. PROVIDE EMERGENCY BACKUP FOR TYPE 'C1' FIXTURES. |
| D | LITHONIA | WDGE2LED-P2-40K-80CRI-T3M-MVOLT-E20WC-BAA-DBLXD | WALL MOUNTED FIXTURE | LED | UNV | 24 | WALL MOUNT | WALL MOUNT FIXTURE AT 10'-6" AFG UNLESS OTHERWISE NOTED. |
| EXIT | LITHONIA | LE-S-W-1-R-EL-N-SD-BAA | EXIT FIXTURE | LED | 120 | 5 | SURFACE | SEE THE DRAWINGS FOR EXACT MOUNTING TYPE/HEIGHT. |
| G | LITHONIA | LDN4SQ-40/30-LS4-WR-LSS-MVOLT-BAA | SQUARE RECESSED DOWNLIGHT | LED | UNV | 33 | RECESSED | |
| S | INVUE | MSA-E02-LED-E1-T2-AP 12" ROUND POLE | POLE MOUNTED PEDESTAL FIXTURE | LED | 120 | 52 | POLE MOUNTED | SEE THE POLE BASE DETAIL FOR ADDITIONAL INFORMATION. |
| T | LITHONIA | DSXF1 LED, P1-40K-MSP-MVOLT1-THK-UBV-DBLXD | WALL MOUNTED FLOOD LIGHT | LED | UNV | 21 | SURFACE | MOUNT FIXTURE TO WEATHERPROOF JUNCTION BOX ON SEAT WALL. FIELD AM FIXTURE TO ILLUMINATE THE FLAG. MOUNT FIXTURE 12" AFG. |




FEEDER SCHEDULE	
MARK	FEEDER DESCRIPTION
①	(2) #1'S & (1) #6 GROUND IN 1 1/2" CONDUIT.
②	(2) 30'S & (1) #3 GROUND IN EACH OF (2) 2" CONDUIT.
③	(2) 6'S & (1) #10 GROUND IN 3/4" CONDUIT.
④	(1) #6'S & (1) #10 GROUND IN 3/4" CONDUIT.
⑤	(2) #10'S & (1) #10 GROUND IN 3/4" CONDUIT.
⑥	GROUND IN ACCORDANCE WITH THE NEC.
⑦	(2) 400MCM IN EACH OF (3) 3" CONDUITS.
⑧	(3) 500MCM & (1) #3 GROUND IN 2 1/2" CONDUIT.
⑨	(2) 3'S & (1) #8 GROUND IN 1" CONDUIT.
⑩	(3) 40'S & (1) #4 GROUND IN 2" CONDUIT.
⑪	(3) 300'S & (1) 10 GROUND IN EACH OF (3) 2 1/2" CONDUITS.



Sidney West-Bound Rest Area
Sidney, Nebraska



EO.00



SITE ELECTRICAL UTILITIES PLAN

SCALE: 1"=30'-0"

SITE ELECTRICAL UTILITIES PLAN NOTES:

- 1 ROUTE #10'S THROUGHOUT ENTIRE CIRCUIT.
- 2 18"x18" IN GROUND PULL BOX. FOR CONNECTION TO OWNER PROVIDED SECURITY CAMERA SYSTEM. CONNECT EACH BOX VIA (1) 2 1/2" CONDUIT. COORDINATE EXACT LOCATIONS WITH THE OWNERS REPRESENTATIVE.
- 3 APPROXIMATE LOCATION OF BUILDING SERVICE ENTRANCE.
- 4 PAD MOUNTED UTILITY TRANSFORMER. COORDINATE WORK WITH THE UTILITY COMPANY.
- 5 24"x24" IN GROUND PULL BOX. FOR CONNECTION TO PARKING LOT/ ROADWAY LIGHTING (INSTALLED AND ROUTED TO BOX BY OTHERS). CONNECT EACH LIGHTING CIRCUIT TO PANELBOARD P-1 VIA (2) #6'S & (1) IN GROUND IN 1" CONDUIT. SEE THE LIGHTING PLAN, PANELBOARD SCHEDULE, LIGHTING CONTROL DIAGRAM AND CONTRACTOR SCHEDULE FOR ADDITIONAL INFORMATION.
- 6 ELECTRICAL CONNECTION TO SEPTIC SYSTEM DOSING PUMPS FROM THE DOSING PUMP CONTROL PANEL. SEE THE CIVIL SHEETS AND THE POWER AND AUXILIARY SYSTEMS PLAN FOR ADDITIONAL INFORMATION. PROVIDE CONNECTIONS FOR CONTROL OF THE PUMPS AND HIGH WATER LEVEL ALARM. ROUTE VIA (1) 1 1/2" CONDUIT.
- 7 ELECTRICAL SECONDARIES. SEE THE ELECTRICAL ONE LINE DIAGRAM FOR ADDITIONAL INFORMATION.
- 8 COORDINATE EXACT LOCATION OF WELL WITH THE WELL SUPPLIER/ CONTRACTOR.



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS


Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A


May 15, 2023





Preliminary

Site Electrical
Utilities Plan

E0.01




LIGHTING PLAN NOTES	
KEY NOTE	DESCRIPTION
1	CONNECT EMERGENCY DRIVER TO AN UNSWITCHED HOT CONDUCTOR OF THE CIRCUIT INDICATED.
2	CONNECT FIXTURE TO AN UNSWITCHED HOT CONDUCTOR OF THE CIRCUIT INDICATED.
3	SEE THE LIGHTING CONTRACTOR SCHEDULE FOR CONTROL CIRCUIT INFORMATION.



Branch Panel: P					Volts: 120/240 Single		A.I.C. Rating: 65,000				
Supply From: DP					Phases: 1		Maine Rating: 225 A				
Mounting: SURFACE					Wires: 3		MCB Rating: Main Lug Only (MLO)				
Enclosure: LIGHTING & APPLIANCE											
CKT	Rating	Poles	Load Name	A		B		Load Name	Poles	Rating	CKT
1	20 A	1	RCPT: OFFICE	1380 VA	1080 VA			RCPT: LOBBY	1	20 A	2
3	20 A	1	MECH: WATER COOLER			180 VA	180 VA	RCPT: LOBBY	1	20 A	4
5	20 A	1	RCPT: VENDING	180 VA	180 VA			RCPT: VENDING	1	20 A	6
7	20 A	1	RCPT: VENDING			180 VA	180 VA	MECH: MENS RESTROOM 102	1	30 A	8
9	30 A	1	MECH: MENS RESTROOM 102	180 VA	180 VA			MECH: WOMENS RR HAND DRYER	1	30 A	10
11	30 A	1	MECH: WOMENS RR HAND DRYER			180 VA	675 VA	MECH: AUTOMATIC VALVES	1	20 A	12
13	20 A	1	RPCT: MAINTENANCE	960 VA	180 VA			MECH FAMILY RR HAND DRYER	1	30 A	14
15	20 A	1	MECH: FAMILY RR HAND DRYER			180 VA	180 VA	MECH WATER SKID	1	20 A	16
17	20 A	2	EH-1	1860 VA	1860 VA			EH-1	2	20 A	18
19	--	--				1860 VA	1860 VA		--	--	20
21	20 A	1	EF-1	792 VA	792 VA			EF-1	1	20 A	22
23	20 A	2	EW-H1			90 VA	1000 VA	RCPT: HW/CP	1	20 A	24
25	--	--	--	90 VA	720 VA			LTG: RRS, MAINTENANCE	1	20 A	26
27	20 A	1	LTG: LOBBY, OFFICE			216 VA	620 VA	LTG: EXTERIOR BLDG LTS	1	20 A	28
29	20 A	1	LTG: RRS	474 VA	0 VA			T1	1	20 A	30
31	20 A	1	LTG NW PARKING/ ROADWAY			1677 VA	1677 VA	LTG NE PARKING/ ROADWAY	1	20 A	32
33	20 A	1	LTG SW PARKING/ ROADWAY	1376 VA	1376 VA			LTG S CENTRAL PARKING/ ROADWAY	1	20 A	34
35	20 A	1	LTG SE PARKING/ ROADWAY			1376 VA	180 VA	MECH WATER SKID	1	20 A	36
37	20 A	1	MECH WATER SKID	180 VA	468 VA			LTG N PED POLES	1	20 A	38
39	20 A	1	C1			1000 VA	531 VA	LTG S PED POLES	1	20 A	40
41	20 A	1	C2	1000 VA	1000 VA			C3	1	20 A	42
43	20 A	1	C4			1000 VA	1000 VA	Lighting Relay Panel Surface	1	20 A	44
45	20 A	1	Spare	0 VA	180 VA			MECH	1	20 A	46
47	20 A	1	Spare			0 VA	0 VA	Spare	1	20 A	48
49	20 A	1	Spare	0 VA	0 VA			Spare	1	20 A	50
51	--	1	Space			--	--	Space	1	--	52
53	--	1	Space	--	--			Space	1	--	54
55	--	1	Space	--	--	--	--	Space	1	--	56
57	--	1	Space	--	--	--	--	Space	1	--	58
59	--	1	Space	--	--	--	--	Space	1	--	60
61	--	1	Space	--	--			Space	1	--	62
63	--	1	Space			--	--	Space	1	--	64
65	--	1	Space	--	--			Space	1	--	66
67	--	1	Space			--	--	Space	1	--	68
69	--	1	Space	--	--	--	--	Space	1	--	70
71	--	1	Space			--	--	Space	1	--	72
Total Load:				16488 VA		16022 VA					
Total Amps:				137 A		134 A					
Load Classification				Connected Load	Demand Factor	Estimated Demand	Panel Totals				
RCPT				5140 VA	125.00%	6425 VA	Total Conn. Load: 27510 VA				
LTG				10511 VA	125.00%	13139 VA	Total Est. Demand: 31423 VA				
MECH				11859 VA	100.00%	11859 VA					
							Total Est. Demand: 131 A				

POWER & AUXILIARY SYSTEMS PLAN NOTES	
KEY NOTE	DESCRIPTION
1	ELECTRICAL CONNECTION TO HAND DRYER. ROUTE #105 THROUGHOUT ENTIRE CIRCUIT.
2	ELECTRICAL CONNECTION TO FLUSH VALVES/LAV FAUCETS. PROVIDE CONNECTION THROUGH WALL TO VALVE ON OTHER SIDE. COORDINATE EXACT ELEVATION AND CONNECTION DETAILS WITH THE MECHANICAL CONTRACTOR.
3	RECESSED WALL BOX (CHIEF PAC #526). PROVIDE BOX WITH (2) DUPLEX RECEPTACLES. ROUTE (2) 1" CONDUITS FROM THE BOX AND STUB INTO THE MAINTENANCE ROOM. BUSH CONDUIT ENDS.
4	ELECTRICAL CONNECTION TO WATERCOOLER. COORDINATE EXACT RECEPTACLE LOCATION WITH THE WATERCOOLER SUPPLIER/INSTALLER.
5	TEMPORARY GENERATOR CONNECTION. SEE THE ONE LINE DIAGRAM FOR ADDITIONAL INFORMATION.
6	SEE THE ELECTRICAL ONE LINE DIAGRAM FOR CONDUIT AND CONDUCTOR SIZE.
7	ELECTRICAL CONNECTION TO WELL CONTRACTOR SUPPLIED VFD CONTROL. SEE THE SITE ELECTRICAL UTILITIES PLAN AND THE ONE LINE DIAGRAM FOR ADDITIONAL INFORMATION.
8	SEPTIC SYSTEM DUREX DOSING PUMP CONTROL PANEL (GLARUS #10-1430). PROVIDE PANEL WITH ABILITY TO SEND HIGH WATER ALERT OUT VIA TEXT/PHONE CALL. SEE THE ELECTRICAL SITE PLAN FOR ADDITIONAL INFORMATION.
9	ELECTRICAL RECEPTACLE FOR CONNECTION TO IRRIGATION CONTROLLER.




CONTACTOR SCHEDULE								
DESIGNATION	LOCATION	SERVES	CIRCUITS	NO. OF POLES	CONTACT RATING	COIL VOLTAGE	CONTROL CIRCUIT	CONTROLLED BY
C1	MAINTENANCE 105	INTERIOR LIGHTING	P-27 P-29	4	30A	120V	P-39 (T1) P-30	T1/P1
C2	MAINTENANCE 105	EXTERIOR LIGHTING	P-28 P-38 P-40	4	30A	120V	P-41	T2/P2
C3	MAINTENANCE 105	PARKING LOT/ ROADWAY LIGHTING NORTH	P-31 P-32	4	30A	240	P-42	P3
C4	MAINTENANCE 105	PARKING LOT/ ROADWAY LIGHTING SOUTH	P-34 P-35	4	30A	240	P-43	P3
								REMARKS
								PROVIDE CONTACTOR RATED FOR CONTINUOUS DUTY OPERATION. SEE LIGHTING CONTROL DIAGRAM FOR ADDITIONAL INFORMATION.
								PROVIDE CONTACTOR RATED FOR CONTINUOUS DUTY OPERATION. SEE LIGHTING CONTROL DIAGRAM FOR ADDITIONAL INFORMATION.
								PROVIDE CONTACTOR RATED FOR CONTINUOUS DUTY OPERATION. SEE LIGHTING CONTROL DIAGRAM FOR ADDITIONAL INFORMATION.
								PROVIDE CONTACTOR RATED FOR CONTINUOUS DUTY OPERATION. SEE LIGHTING CONTROL DIAGRAM FOR ADDITIONAL INFORMATION.

SHEET HISTORY:
ISSUED 05/15/2023 Construction Documents

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area
Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary


Electrical Plans

E1.11



1 MOUNTING LOCATIONS


SCALE: 1/2" = 1'-0"



2 RESTROOM SIGNAGE

SCALE: 6" = 1'-0"

ASI SIGNAGE:
BASIS OF DESIGN: ASI SIGNAGE INNOVATIONS
SIGN SERIES: INTOUCH SERIES - EXTERIOR RATED
BACKGROUND COLOR: SATIN ALUMINUM, MX-15
TEXT/GRAPHIC COLOR: MX-09
TYPESTYLE: HELVETICA MEDIUM
TEXT HEIGHT: 5/8"
MOUNTING METHOD: COUNTER-SUNK MECHANICAL FASTENERS
PROVIDE BRAILLE TEXT BELOW TYPE




3 ROOM IDENTIFICATION SIGN

SCALE: 6" = 1'-0"

ASI SIGNAGE:
BASIS OF DESIGN: ASI SIGNAGE INNOVATIONS
SIGN SERIES: INTOUCH SERIES - EXTERIOR RATED
BACKGROUND COLOR: SATIN ALUMINUM, MX-15
TEXT/GRAPHIC COLOR: MX-09
TYPESTYLE: HELVETICA MEDIUM
TEXT HEIGHT: 5/8"
MOUNTING METHOD: COUNTER-SUNK MECHANICAL FASTENERS
PROVIDE BRAILLE TEXT BELOW TYPE

B1, B2, B3



4 FIRST FLOOR FINISH PLAN

SCALE: 1/4" = 1'-0"

ROOM FINISH SCHEDULE

ROOM NO.	ROOM NAME	FLOOR			NORTH WALL		EAST WALL		SOUTH WALL		WEST WALL		CEILING		REMARK NO.
		MTL.	FIN.	BASE	MTL.	FIN.	MTL.	FIN.	MTL.	FIN.	MTL.	FIN.	MTL.	FIN.	
100	LOBBY	CONCRETE	POLISHED	SSM-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	GPDW	PT-1	
101	TOURISM OFFICE	CONCRETE	POLISHED	SSM-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	GPDW	PT-1	
102	MEN'S RESTROOM	CONCRETE	POLISHED	SSM-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	GPDW	PT-1	
103	EQUIPMENT ROOM	CONCRETE	SEALER	N/A	CMU, GPDW	PT-1	CMU, GPDW	PT-1	CMU, GPDW	PT-1	CMU, GPDW	PT-1	GPDW	PT-1	
104	FAMILY RESTROOM	CONCRETE	POLISHED	SSM-2	BURNISHED CMU	SEALER	BURNISHED CMU	SEALER	BURNISHED CMU	SEALER	BURNISHED CMU	SEALER	GPDW	PT-1	
105	MAINTENANCE ROOM	CONCRETE	SEALER	N/A	CMU, GPDW	PT-1	CMU, GPDW	PT-1	CMU, GPDW	PT-1	CMU, GPDW	PT-1	GPDW	PT-1	
106	FAMILY RESTROOM	CONCRETE	POLISHED	SSM-2	BURNISHED CMU	SEALER	BURNISHED CMU	SEALER	BURNISHED CMU	SEALER	BURNISHED CMU	SEALER	GPDW	PT-1	
107	WOMEN'S RESTROOM	CONCRETE	POLISHED	SSM-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	BURNISHED CMU, GPDW	SEALER PT-2	GPDW	PT-1	

ROOM FINISH GENERAL NOTES

- PAINTE ALL HOLLOW METAL DOORS & FRAMES W/ HIGH PERFORMANCE COATING TO MATCH CLEAR ANODIZED ALUMINUM STOREFRONT WINDOW SYSTEM.
- RUBBER BASE SHALL NOT BE APPLIED TO CMU AND CONCRETE WALLS, TYP.
- SEE INTERIOR ELEVATIONS AND FINISH FLOOR PLAN FOR EXTENT OF PAINT AND WALL COVERING FINISHES DESIGNATED ON FINISH SCHEDULE.
- SEE INTERIOR WALL ELEVATIONS AND FINISH FLOOR PLAN FOR EXTENT OF TILE FINISHES.
- SEE REFLECTED CEILING PLAN.

SIGNAGE SCHEDULE

SIGN LOCATION			SIGN COPY			
ROOM NAME	ROOM NUMBER	TYPE	SIGN TEXT	SIGN RM NUMBER	APPLICATION	COMMENTS
TOURISM OFFICE	101	B1	TOURISM OFFICE	101	WALL	RECESSED INTO THE CMU WALL
MEN'S RESTROOM	102	A1	MEN	102	WALL	RECESSED INTO THE CMU WALL
EQUIPMENT ROOM	103	B3	EQUIPMENT ROOM	103	WALL	
FAMILY RESTROOM	104	A3	FAMILY RESTROOM	104	WALL	RECESSED INTO THE CMU WALL
MAINTENANCE ROOM	105	B2	MAINTENANCE ROOM	105	WALL	RECESSED INTO THE CMU WALL
FAMILY RESTROOM	106	A3	FAMILY RESTROOM	106	WALL	RECESSED INTO THE CMU WALL
WOMEN'S RESTROOM	107	A2	WOMEN	107	WALL	RECESSED INTO THE CMU WALL

FINISHES

PAINT		PLASTIC LAMINATE	
PT-1	MANUFACTURER: SHERWIN WILLIAMS	PL-1	MANUFACTURER: WILSONART LAMINATE
	HUE: BRIGHT WHITE		PATTERN: D92-60 DOVE GREY
	FINISH: --		APPLICATION: CASEWORK SHELLS
PT-2	MANUFACTURER: SHERWIN WILLIAMS	PL-2	MANUFACTURER: WILSONART LAMINATE
	HUE: SW 7020 BLACK FOX		PATTERN: 4942-38 CRISP LINEN
	FINISH: --		APPLICATION: COUNTERTOP
PT-3	MANUFACTURER: SHERWIN WILLIAMS	PL-3	MANUFACTURER: NEVAMAR
	HUE: SW 7020 BLACK FOX		PATTERN: WROUGHT IRON, S6054T, TEXTURED
	FINISH: --		APPLICATION: TOEKICK
HIGH PERFORMANCE COATINGS		PL-4	MANUFACTURER: WILSONART LAMINATE
HPC-1	MANUFACTURER: SEE HIGH PERFORMANCE SPECIFICATIONS		PATTERN: D354-60 DESIGNER WHITE
	PRODUCT: GRAFFITI AND SEALER		APPLICATION: DRAWER BOTTOMS
	APPLICATION: BURNISHED BLOCK WALLS		
HPC-2	MANUFACTURER: SEE HIGH PERFORMANCE SPECIFICATIONS	SSM-1	MANUFACTURER: CORIAN
	PRODUCT: METALLIC TO MATCH CLEAR ANODIZED		PRODUCT: --
	APPLICATION: HOLLOW METAL DOORS & FRAMES		COLORWAY: SILVER BIRCH
HPC-3	MANUFACTURER: SEE HIGH PERFORMANCE SPECIFICATIONS	SSM-2	MANUFACTURER: CORIAN
	PRODUCT: --		APPLICATION: FAMILY RESTROOM VANITIES
	APPLICATION: --		
BURNISHED CMU		SSM-2	MANUFACTURER: CORIAN
BURNISHED CMU	MANUFACTURER: COUNTRY MATERIALS		PRODUCT: --
	PRODUCT: PREMIER ULTRA BURN, MASONRY UNITS		COLORWAY: ASH AGGREGATE
	MORE INFO: REFERENCE DETAIL 3, SHEET A2.10		APPLICATION: WALL BASE

ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A


May 15, 2023



Preliminary

First Floor Finishes Plan

F1.11



SITE EXISTING CONDITIONS/ DEMOLITION PLAN

SCALE: 1" = 50'-0"

GENERAL NOTES:

- THE GENERAL CONTRACTOR SHALL VERIFY ALL EXISTING SITE CONDITIONS SHOWN ON PLAN. ANY DISCREPANCIES NOTED IN THE FIELD SHALL BE RELAYED TO THE LANDSCAPE ARCHITECT AND OWNER PRIOR TO THE COMMENCEMENT OF WORK.
- THE GENERAL CONTRACTOR SHALL PRESERVE AND PROTECT ALL EXISTING UTILITIES TO REMAIN DURING CONSTRUCTION. UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND RECORD DRAWINGS RECEIVED. THE SURVEYOR MAKES NO GUARANTEES THAT THE UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UTILITIES ARE SHOWN IN THE EXACT LOCATION INDICATED, ALTHOUGH THE SURVEYOR DOES CERTIFY THAT THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM INFORMATION AVAILABLE. THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES. THIS INCLUDES PRIVATE AND PUBLIC UTILITIES. FURTHER VERIFICATION MAY BE REQUIRED TO IDENTIFY UTILITIES NOT SHOWN HEREIN. THE CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED THROUGH THE "ONE CALL" SYSTEM. CALL THE UNDERGROUND HOTLINE FOR UTILITY LOCATIONS AT 1-800-331-5966. FIELD VERIFY ALL SITE SPECIFIC UTILITIES.
- THE GENERAL CONTRACTOR SHALL NOT REMOVE OR ALTER ANY PROTECTION FENCING WITHOUT PRIOR WRITTEN CONSENT FROM OWNER AND LANDSCAPE ARCHITECT.
- FILL AND CUT AREAS SHALL BE STRIPPED OF ALL VEGETATION AND TOPSOIL PRIOR TO COMMENCEMENT OF WORK. ALL TOPSOIL SHALL BE REDISTRIBUTED AFTER ROUGH GRADING IS COMPLETED. PRESERVE AND PROTECT THE REDISTRIBUTED TOPSOIL FOR CONSTRUCTION ACTIVITY. MACHINERY SHALL NOT BE ALLOWED TO DRIVE OVER IT.
- PROVIDE POSITIVE DRAINAGE AT ALL TIMES WITHIN THE CONSTRUCTION AREA. DO NOT ALLOW WATER TO FLOW OR POND IN EXCAVATION AREAS.

DEMOLITION NOTES

- CONTRACTOR TO PRESERVE ALL SURVEY CONTROL POINTS.
- CONTRACTOR MUST PROTECT THE PUBLIC AT ALL TIMES WITH FENCING, SIGNING, BARRICADES, ENCLOSURES, ETC. TO THE BEST PRACTICES AND APPROVED BY THE NEBRASKA DEPARTMENT OF TRANSPORTATION.
- CONTINUOUS PEDESTRIAN & VEHICULAR ACCESS SHALL BE MAINTAINED AT ALL TIMES DURING SITE DEMOLITION AND CONSTRUCTION.
- DAMAGE TO ALL EXISTING CONDITIONS TO REMAIN WILL BE REPLACED AT CONTRACTOR'S EXPENSE.
- THE CONTRACTOR IS RESPONSIBLE FOR THE DEMOLITION, REMOVAL, AND DISPOSING IN A LOCATION APPROVED BY ALL GOVERNING AUTHORITIES OF FENCE, FLUMES, FOUNDATIONS, DRIVES, DRAINAGE STRUCTURES, UTILITIES, ETC. (EXCEPT WHERE NOTED BY ENGINEER), SUCH THAT THE IMPROVEMENTS SHOWN ON THE REMAINING PLANS CAN BE CONSTRUCTED. ALL FACILITIES TO BE REMOVED SHALL BE UNDERCUT TO SUITABLE MATERIAL AND BROUGHT TO GRADE WITH SUITABLE COMPACTED FILL MATERIAL PER THE NEBRASKA DEPARTMENT OF TRANSPORTATION SPECIFICATIONS.
- THE CONTRACTOR IS RESPONSIBLE FOR REMOVING ALL DEBRIS FROM THE SITE AND DISPOSING THE DEBRIS IN A LAWFUL MANNER. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL PERMITS REQUIRED FOR THE DEMOLITIONS AND DISPOSAL.
- ALL EXISTING SEWERS, PIPING AND UTILITIES SHOWN ARE NOT TO BE INTERPRETED AS THE EXACT LOCATION, OR AS THE ONLY OBSTACLES THAT MAY OCCUR ON THE SITE. VERIFY EXISTING CONDITIONS AND PROCEED WITH CAUTION AROUND ANY ANTICIPATED FEATURES. GIVE NOTICE TO ALL UTILITY COMPANIES REGARDING DESTRUCTION AND REMOVAL OF ALL SERVICE LINES AND CAP ALL LINES BEFORE PROCEEDING WITH THE WORK. UTILITIES DETERMINED TO BE ABANDONED AND LEFT IN PLACE SHALL BE GROUTED IF UNDER BUILDING.
- ELECTRICAL, TELEPHONE, CABLE, WATER, FIBER OPTIC CABLE AND/OR GAS LINES NEEDING TO BE REMOVED, RELOCATED, AND/OR ABANDONED SHALL BE COORDINATED WITH THE AFFECTED UTILITY COMPANY. ADEQUATE TIME SHALL BE PROVIDED FOR RELOCATION AND CLOSE COORDINATION WITH THE UTILITY COMPANY IS NECESSARY TO PROVIDE A SMOOTH TRANSITION IN UTILITY SERVICE. CONTRACTOR SHALL PAY CLOSE ATTENTION TO EXISTING UTILITIES WITHIN THE CONSTRUCTION LIMITS DURING CONSTRUCTION. THE CONTRACTOR SHALL COORDINATE WITH THE UTILITY COMPANY CONCERNING PORTIONS OF WORK WHICH MAY BE PERFORMED BY THE UTILITY COMPANY'S FORCES.
- ALL SIDEWALK & PAVEMENT TO REMAIN SHALL BE PROTECTED IN PLACE INCLUDING PROTECTION FROM DAMAGE CAUSED BY REMOVAL OF ABUTTING CONCRETE. THE CONTRACTOR SHALL SAW CUT AT NEAREST JOINT WHERE NECESSARY.

SYMBOLS LEGEND:

PROPERTY LINE
LIMITS OF CONSTRUCTION



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
Feb. 24, 2023



Preliminary

Site Existing Conditions/
Demolition Plan


L1.01




SITE LAYOUT PLAN

SCALE: 1" = 20'-0"

PAVEMENT LEGEND:



5' TH CONCRETE PAVEMENT
STANDARD GRAY



5' TH REINFORCED CONCRETE PAVEMENT
W/ EPOXY COATED #4'S EACH WAY @ 18" O.C.
STANDARD GRAY

CURB RAMP: PROVIDE A MIN 6' WIDE LANDING AT TOP OF CURB RAMP. LANDING SLOPE TO BE LESS THAN 2% IN ALL DIRECTIONS, TYP.
DO NOT INSTALL DETECTABLE WARNING PANEL ON THIS RAMP, SIMILAR TO DETAIL 10.
REF DETAIL 10.
L6.01

PARKING LOT PAVT BY OTHERS

5' TH CONC P/MT. SPACE C/S EVENLY AS SHOWN, TYP., REF DETAIL 1-3.
L6.01

ADA CURB RAMP: TYP OF 3. PROVIDE A MIN 6' WIDE LANDING AT TOP ADA CURB RAMP. LANDING SLOPE TO BE LESS THAN 2% IN ALL DIRECTIONS, TYP., REF DETAIL 10.
L6.01

N 480535.78
E 835587.74
N 480505.41
E 835588.39
N 480505.41
E 835534.77

REST AREA BUILDING
ARCH FFE: 100'0"
ENG FFE: 4222.60

N 480454.14
E 835534.77
N 480454.14
E 835588.39

5' TH CONC P/MT. SPACE C/S EVENLY AS SHOWN, TYP., REF DETAIL 1-3.
L6.01

NEBRASKA HONORS OUR TROOPS SIGN, REF DETAIL 4-9.
L6.01

HISTORICAL PLAQUE WALL, 4-9.
REF DETAIL 4-9.
L6.01

FLAG POLE, TYP OF 3.
PURPLE HEART PLAQUE AND SIGN, 4-9.
REF DETAIL 4-9.
L6.01

N 480508.78
E 835620.50
N 480500.75
E 835754.85

N 480479.78
E 835891.43


5' TH CONC P/MT. SPACE C/S EVENLY AS SHOWN, TYP., REF DETAIL 1-3.
L6.01

ADA CURB RAMP: TYP OF 3. PROVIDE A MIN 6' WIDE LANDING AT TOP ADA CURB RAMP. LANDING SLOPE TO BE LESS THAN 2% IN ALL DIRECTIONS, TYP., REF DETAIL 10.
L6.01

5' TH REINFORCED CONC P/MT. SPACE C/S EVENLY AS SHOWN, TYP., REF DETAIL 1-3.
L6.01

5' TH CONC P/MT. SPACE C/S EVENLY AS SHOWN, TYP., REF DETAIL 1-3.
L6.01

PARKING LOT PAVT BY OTHERS



SHEET HISTORY:

ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
05/15/2023



Preliminary

Site Layout Plan

L2.01



SITE GRADING PLAN

SCALE: 1" = 20'-0"

GENERAL NOTES:

1. THE GENERAL CONTRACTOR SHALL VERIFY ALL EXISTING SITE CONDITIONS SHOWN ON PLAN. ANY DISCREPANCIES NOTED IN THE FIELD SHALL BE RELAYED TO THE LANDSCAPE ARCHITECT AND OWNER PRIOR TO THE COMMENCEMENT OF WORK.
2. THE GENERAL CONTRACTOR SHALL PRESERVE AND PROTECT ALL EXISTING UTILITIES TO REMAIN DURING CONSTRUCTION. UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND RECORD DRAWINGS RECEIVED. THE SURVEYOR MAKES NO GUARANTEES THAT THE UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN-SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UTILITIES ARE SHOWN IN THE EXACT LOCATION INDICATED. ALTHOUGH THE SURVEYOR DOES CERTIFY THAT THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM INFORMATION AVAILABLE, THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES. THIS INCLUDES PRIVATE AND PUBLIC UTILITIES. FURTHER VERIFICATION MAY BE REQUIRED TO IDENTIFY UTILITIES NOT SHOWN HEREIN. THE CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED THROUGH THE "ONE CALL" SYSTEM. CALL THE UNDERGROUND HOTLINE FOR UTILITY LOCATIONS AT 1-800-331-5666. FIELD VERIFY ALL SITE SPECIFIC UTILITIES.
3. THE GENERAL CONTRACTOR SHALL NOT REMOVE OR ALTER ANY PROTECTION FENCING WITHOUT PRIOR WRITTEN CONSENT FROM OWNER AND LANDSCAPE ARCHITECT.
4. FILL AND CUT AREAS SHALL BE STRIPPED OF ALL VEGETATION AND TOPSOIL PRIOR TO COMMENCEMENT OF WORK. ALL TOPSOIL SHALL BE REDISTRIBUTED AFTER ROUGH GRADING IS COMPLETED. PRESERVE AND PROTECT THE REDISTRIBUTED TOPSOIL FOR CONSTRUCTION ACTIVITY. MACHINERY SHALL NOT BE ALLOWED TO DRIVE OVER IT.
5. PROVIDE POSITIVE DRAINAGE AT ALL TIMES WITHIN THE CONSTRUCTION AREA. DO NOT ALLOW WATER TO FLOW OR POND IN EXCAVATION AREAS.
6. A MAXIMUM OF 2% CROSS SLOPE SHALL BE ALLOWED FOR ALL SIDEWALKS.

ADA GRADING NOTES

ADA SIDEWALKS

ALL AREAS OF THE ADA ACCESSIBLE PATH ARE REQUIRED TO BE LESS THAN 2% SLOPE IN THE DIRECTION OF TRAVEL AND LESS THAN 2% FOR CROSS SLOPES. CONTRACTOR IS RESPONSIBLE TO CONSTRUCT ALL ADA IMPROVEMENTS PER PLAN. ANY PORTIONS OF DESIGNATED ADA ACCESSIBLE PATHS THAT EXCEED THESE REQUIREMENTS WILL REQUIRE REMOVAL AND REPLACEMENT AT THE CONTRACTORS EXPENSE.


ADA LANDINGS

ALL ADA ACCESSIBLE LANDINGS ARE REQUIRED TO BE LESS THAN 2% IN ALL DIRECTIONS. CONTRACTOR IS RESPONSIBLE TO CONSTRUCT ALL ADA IMPROVEMENTS PER PLAN. ANY PORTIONS OF DESIGNATED ADA ACCESSIBLE PATHS THAT EXCEED THESE REQUIREMENTS WILL REQUIRE REMOVAL AND REPLACEMENT AT THE CONTRACTORS EXPENSE.

ADA CURB RAMPS

ALL ADA RAMPS ARE REQUIRED TO HAVE SLOPES LESS THAN 8.33% IN THE DIRECTION OF TRAVEL AND LESS THAN 2% FOR CROSS SLOPES. CONTRACTOR IS RESPONSIBLE TO CONSTRUCT ALL ADA IMPROVEMENTS PER PLAN. ANY PORTIONS OF DESIGNATED ADA ACCESSIBLE PATHS THAT EXCEED THESE REQUIREMENTS WILL REQUIRE REMOVAL AND REPLACEMENT AT THE CONTRACTORS EXPENSE.

GRADING LEGEND



SPOT ELEVATION LEGEND

SYMBOL	DESCRIPTION
PVMT	TOP OF PAVEMENT
TS	TOP OF STEP
BS	BOTTOM OF STEP
ME	MATCH EXISTING
TC	TOP OF CURB
BC	BOTTOM OF CURB
TW	TOP OF WALL
BW	BOTTOM OF WALL/FINISH GRADE
DOOR	FINISH FLOOR ELEVATION
BP	BREAK POINT
HP	HIGH POINT
LP	LOW POINT
GDE	FINISH GRADE



SHEET HISTORY:

ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary

Site Grading Plan

L3.01



 **TREE/ TURF SITE PLANTING PLAN**
SCALE: 1" = 50'-0"

GENERAL NOTES:

1. CONTRACTOR SHALL MULCH ALL TREE, SHRUB AND PERENNIAL BEDS. REFER TO PLANTING INSTALLATION DETAILS, THIS SHEET.
2. PROVIDE A CULTIVATED EDGE FOR ALL PLANTING BED AREAS EDGES THAT AREA ADJACENT TO TURF AREAS AS WELL AS ALONG THE EDGES OF CURBS, SIDEWALKS AND OTHER PAVEMENT AREAS.
3. PROVIDE 6" OF TOPSOIL IN ALL SOD AND SEED AREAS.
4. PROVIDE 24" OF TOPSOIL IN ALL PLANTING BED AREAS.




SOD

FESCUE & KENTUCKY BLUE GRASS BLEND

SEED MIXTURE SHALL INCORPORATE A MINIMUM OF:
- 3 OF THE TOP 25% PERFORMING TALL GRASS FESCUE
70%-95% OF TOTAL SEED MIXTURE

- 1 OF THE TOP 25% PERFORMING KENTUCKY BLUE GRASS
5%-30% OF TOTAL SEED MIXTURE

PERFORMANCE SHALL BE BASED ON NTEPS 2015 TURF
GRASS RANKINGS.




SEED TYPE 'D' NATIVE GRASS

SEED TYPE 'D'
COORDINATE WITH LANDSCAPE ARCH AND NDOT
FOR EXACT NATIVE GRASS SEED MIX


TREE PLANTING NOTES:

1. DO NOT HEAVILY PRUNE THE TREE AT PRUNING. PRUNE ONLY CROSSOVER LIMBS, CO-DOMINANT LEADERS, & BROKEN OR DEAD BRANCHES. SOME INTERIOR TWIGS & LATERAL BRANCHES MAY BE PRUNED. DO NOT REMOVE THE TERMINAL BUDS OF BRANCHES THAT EXTEND TO THE EDGE OF THE CROWN.
2. MARK THE NORTH SIDE OF THE TREE IN THE NURSERY, AND ROTATE TREE TO FACE NORTH AT THE SITE WHENEVER POSSIBLE.
3. SET TOP OF ROOT BALL 1.2 INCHES HIGHER THAN SURROUNDING GRADE.
4. APPLY 3"TH WOOD MULCH. DO NOT PLACE MULCH IN DIRECT CONTACT w/ TREE TRUNK.
5. APPLY TREE WRAP TO TRUNK FROM THE BTM UPWARD, SECURE w/ TAPE.
6. EACH TREE MUST BE PLANTED SUCH THE TRUNK FLARE IS VISIBLE AT THE TOP OF THE ROOT BALL. TREES WHERE THE FLARE IS NOT VISIBLE SHALL BE REJECTED. DO NOT COVER THE TOP OF THE ROOT BALL w/ SOIL.
7. REMOVE ALL TWINE, ROPE, WIRE AND BURLAP FROM THE UPPER 1/3 OF ROOT BALL. (REMOVE WIRE BASKETS)
8. PLACE ALL ROOT BALLS ON UN-EXCAVATED OR TAMPED SOIL, TYP



STAKING REQUIREMENTS:

- 1) STAKING SHALL BE w/ APPROVAL OF LANDSCAPE ARCH. IF TREE WILL NOT BE ABLE TO SUPPORT ITSELF (DEPENDS ON SPECIES)
- 2) WIRE / CABLE SHALL BE GALV. 14-GAUGE FOR TREES UNDER 2 1/2" CAL. 12-GAUGE FOR TREES OVER 3" CAL
- 3) TIGHTEN WIRE / CABLE ONLY ENOUGH TO KEEP FROM SLIPPING. ALLOW FOR SOME TRUNK MOVEMENT
- 4) PLASTIC HOSE SHALL BE LONG ENOUGH TO ACCOMMODATE 1 1/2" OF GROWTH
- 5) STAKES SHALL BE 1 1/2"x 1 1/2" HARDWOOD OR EQUAL



PLANTING BED NOTES:

- 1) REMOVE TOP 24" OF SOIL & REPLACE w/ NEW TOP SOIL PER SPECIFICATION.
- 2) BLEND TOP SOIL INTO EXISTING SOIL TO A DEPTH OF 24"
- 3) THOROUGHLY MIX COMPOST IN TOP 3-4" OF SOIL
- 4) APPLY 3" LAYER OF MULCH. DO NOT COVER PLANTS.

SHRUB PLANTING NOTES:

- 1) SET SHRUB AT SAME DEPTH AT WHICH IT GREW IN THE FIELD OR CONTAINER.
- 2) PRUNE, THIN & SHAPE SHRUBS IN ACCORDANCE w/ STANDARD HORTICULTURAL PRACTICE.


INITIAL WATERING:

WHEN BACKFILL IS 2/3 COMPLETE, WATER THOROUGHLY UNTIL NO MORE IS ABSORBED

1 PLANTING INSTALLATION DETAILS

SCALE: 1/2"=1'-0"

(IN ALL SOIL TYPES)



2 CULTIVATED MULCH EDGE

SCALE: 3/4"=1'-0"



PLANT LIST

SYMBOL	BOTANICAL NAME	COMMON NAME	SIZE & METHOD OF HANDLING	DESIGN SPREAD & HEIGHT
TREES				
GDE	GYMNOCLADUS DIOCLUS 'ESPRESSO'	ESPRESSO KENTUCKY COFFEETREE	2" CAL., B&B, 12-14' HT RANGE	30' W x 35' H
MC	MALUS CENTZAN	CENTURION CRABAPPLE	1 1/2" CAL., B&B, 6-8' HT RANGE	20' W x 20' H
MP	MALUS PRAIRIEFIRE	PRAIRIEFIRE CRABAPPLE	1 1/2" CAL., B&B, 6-8' HT RANGE	20' W x 20' H
PGD	PICEA GLAUCA 'DENSATA'	BLACK HILLS SPRUCE	6" HT, B&B	20' W x 30' H
QM	QUERCUS MACROCARPA	BUR OAK	2" CAL., B&B, 12-14' HT RANGE	50' W x 50' H
SHRUBS				
AME	ARONIA MELANOCARPA 'ELATA'	BLACK CHOKEBERRY	#2 CONT: 18" HT MIN W/ 3 CANES	5' W x 5' H
PB	PRUNUS BESSEYI	PAWNEE BUTTES SAND CHERRY	#2 CONT: 12" HT MIN W/ 4 CANES	4' W x 18" H
GRASSES				
SSTB	SCHIZACHYRIUM SCOPARIUM 'THE BLUES'	THE BLUES LITTLE BLUESTEM	NO. 1 CONTAINER, 24" SPACING	24" W x 36" H
SH	SPYRODOLUS HETEROLEPIS	PRAIRIE DROPSIED	NO. 1 CONTAINER, 24" SPACING	24" W x 24" H



SHRUB/ ORNAMENTAL GRASS SITE PLANTING PLAN

SCALE: 1" = 20'-0"



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A

May 15, 2023



Preliminary

Tree/ Turf
Site Planting Plan &
Shrub/ Ornamental Grass
Site Planting Plan

L4.01



SITE IRRIGATION PLAN

SCALE: 1" = 20'-0"

IRRIGATION SCHEDULE

SYMBOL	MANUFACTURER/MODEL	QTY
	HUNTER MP STRIP PROS-06-PRS40-CV	1
	HUNTER MP1000 PROS-06-PRS40-CV	44
	HUNTER MP2000 PROS-06-PRS40-CV	17
	HUNTER MP800SR PROS-06-PRS40-CV	5
SYMBOL	MANUFACTURER/MODEL	QTY
	HUNTER I-20-04 1.5	14
	HUNTER I-20-04 2.5	2
	HUNTER I-20-04 3.0	30
	HUNTER I-20-04 6.0	23
	HUNTER I-20-04-LA 2.5	4
	HUNTER I-20-04-LA 3.5	1
SYMBOL	MANUFACTURER/MODEL	QTY
	HUNTER PCZ-101-40 1" W/ EZ-1 DECODER	2
	AREA TO RECEIVE DRIPLINE	1,582 L.F.
	HUNTER HDL-06-12(18)-CV	
SYMBOL	MANUFACTURER/MODEL	QTY
	HUNTER PGV-101G 1" W/ EZ-1 DECODER	14
	HUNTER HQ-SRC 1"	11
	ISOLATION GATE VALVE	3
	FEBCO 825Y 1-1/2"	1
	HUNTER HCC TWO WIRE CONTROLLER	1
	HUNTER WR-CLK	1
	POC BOX - CALL 402.639.9473 FOR INFORMATION	1
	POINT OF CONNECTION 1 1/2"	1
	IRRIGATION LATERAL LINE: POLYETHYLENE PIPE 100 PSI 1"	2,825 L.F.
	IRRIGATION LATERAL LINE: PVC CLASS 200 SDR 21 1 1/4"	373.1 L.F.
	IRRIGATION MAINLINE: PVC CLASS 200 SDR 21 1 1/2"	1,128 L.F.
	PIPE SLEEVE: PVC SCHEDULE 40 2"	19.3 L.F.
	PIPE SLEEVE: 400-35-PVC-20 GREEN CELL CORE 4"	50.8 L.F.
	Valve Callout	
	Valve Number	
	Valve Flow	
	Valve Size	


CRITICAL ANALYSIS

Generated:	2023-05-10 09:37
P.O.C. NUMBER: 01	
Water Source Information:	
Flow Available:	25 GPM
Custom Max Flow:	25 GPM
Flow Available:	25 GPM
Pressure Available:	70 PSI
Static Pressure at POC:	70 PSI
Pressure Available:	70 PSI
DESIGN ANALYSIS	
Maximum Station Flow:	24.65 GPM
Flow Available at POC:	25 GPM
Residual Flow Available:	0.35 GPM
Critical Station:	6
Design Pressure:	45 PSI
Friction Loss:	3.15 PSI
Fittings Loss:	0.31 PSI
Elevation Loss:	0 PSI
Loss through Valve:	4.42 PSI
Pressure Req. at Critical Station:	52.9 PSI
Loss for Fittings:	0.22 PSI
Loss for Main Line:	2.19 PSI
Loss for POC to Valve Elevation:	0 PSI
Loss for Backflow:	12.2 PSI
Critical Station Pressure at POC:	67.5 PSI
Pressure Available:	70 PSI
Residual Pressure Available:	2.51 PSI

IRRIGATION NOTES

- IRRIGATION SYSTEM DESIGN BASED ON 24 GPM AT 70 PSI.
- IRRIGATION DESIGN IS FROM THE POINT OF CONNECTION (POC) ONLY. THE DESIGN IS BASED ON GALLONS PER MINUTE (GPM) AND POUNDS PER SQUARE INCH (PSI) FURNISHED BY OTHERS.
- IRRIGATION CONTRACTOR IS TO VERIFY POINT OF CONNECTION IN THE FIELD. INSTALLER IS TO CONFIRM THE MINIMUM DISCHARGE REQUIREMENTS OF THE POINT OF CONNECTION AS INDICATED ON THE LEGEND PRIOR TO INSTALLATION.
- THE PRESSURE REQUIREMENT AT THE POINT OF CONNECTION IS BASED ON NO MORE THAN 5-FEET OF ELEVATION CHANGE IN THE AREAS OF IRRIGATION.
- ALL PRODUCTS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS AND ACCORDING TO LOCAL BUILDING, ELECTRICAL AND PLUMBING CODES.
- IRRIGATION CONTRACTOR WILL ARRANGE INSPECTIONS REQUIRED BY LOCAL AGENCIES AND ORDINANCES DURING THE COURSE OF CONSTRUCTION AS REQUIRED. ALL WIRING TO BE PER LOCAL CODE. BACKFLOW PREVENTION PER LOCAL CODE.
- LOCATION OF IRRIGATION COMPONENTS SHOWN ON DRAWINGS IS APPROXIMATE. ACTUAL PLACEMENT MAY VARY SLIGHTLY AS REQUIRED TO ACHIEVE FULL, EVEN COVERAGE.
- ALL SPRINKLER HEADS SHALL BE INSTALLED PERPENDICULAR TO FINISH GRADES, EXCEPT AS OTHERWISE INDICATED.
- INSTALL IRRIGATION MAINS WITH A MINIMUM 18" OF COVER BASED ON FINISH GRADES. INSTALL IRRIGATION LATERALS WITH A MINIMUM 12" OF COVER BASED ON FINISH GRADES.
- PIPE LOCATIONS ARE DIAGRAMMATIC. VALVES AND MAINLINE SHOWN IN PAVED AREAS ARE FOR GRAPHIC CLARITY ONLY.
- THE IRRIGATION CONTRACTOR SHALL COMPLY WITH PIPE SIZES AS INDICATED.
- THE FOLLOWING SHOULD BE NOTED REGARDING TO PIPE SIZING: IF A SECTION OF UN-SIZED LATERAL PIPE IS LOCATED BETWEEN TWO IDENTICALLY SIZED SECTIONS THE UN-SIZED SECTION SHALL BE OF THE SAME SIZE. IF A SECTION OF UN-SIZED LATERAL PIPE IS NOT SIZED AT THE END OF A ZONE AND IS NOT BETWEEN TWO IDENTICALLY SIZED SECTIONS THE UN-SIZED SECTION(S) SHALL BE 1-INCH.
- ALL WIRE SPLICES OR CONNECTIONS SHALL BE MADE WITH APPROVED WATERPROOF WIRE CONNECTORS AND BE IN A VALVE OR SPLICE BOX.
- ALL CONTROL WIRING DOWNSTREAM OF THE CONTROLLER IS TO BE 2-WIRE, UL APPROVED DIRECT BURY.
- THE DESIGN IS BASED ON THE SITE INFORMATION AND/OR DRAWING SUPPLIED WITH THE DESIGN CRITERIA BEING SET (AREA TO BE IRRIGATED, EQUIPMENT MANUFACTURER AND MODEL TO BE USED, WATER SOURCE INFORMATION, ELECTRICAL POWER AVAILABILITY, ETC.). SITEONE LANDSCAPE SUPPLY BEARS NO RESPONSIBILITY OR LIABILITY FOR ANY ERRORS IN DESIGN OR INSTALLATION THAT ARISE DUE TO INACCURACIES IN THE ABOVE REFERENCED INFORMATION SUPPLIED TO SITEONE LANDSCAPE SUPPLY IN RELATION TO THIS PROJECT, UNLESS OTHERWISE NOTED.
- BACKFLOW IS PROVIDED AND INSTALLED BY OTHERS.

IRRIGATION NOTE:
IRRIGATION DESIGN AND DETAILING
PROVIDED BY SITE ONE PROJECT SERVICES.
PHONE: 402.213.6094



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound
Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A











May 15, 2023



Preliminary

Site Irrigation Plan

L5.01



L6.01

MECHANICAL ABBREVIATIONS AND SYMBOLS LEGEND						
ABBREVIATIONS		ABBREVIATIONS		PIPING	SHEET METAL	TEMPERATURE CONTROL
A COMPRESSED AIR	OA OUTSIDE AIR	101 BALL VALVE	120 RECTANGULAR DUCT - FIRST NUMBER INDICATES SIZE SHOWN	100 CONTROL POINT	FIRE SUPPRESSION	
AD AREA DRAIN	OAT OUTSIDE AIR TEMPERATURE	102 GATE VALVE	120 ROUND DUCT	101 AIRFLOW MEASURING STATION		
AFF ABOVE FINISHED FLOOR	OB0 MANUAL OPPOSED BLADE BALANCING DAMPER	103 GLOBE VALVE	120 OVAL DUCT - FIRST NUMBER INDICATES SIZE SHOWN	102 CARBON DIOXIDE SENSOR	SCHEMATICS	
AI ANALOG INPUT	PC PLUMBING CONTRACTOR	104 BUTTERFLY VALVE	120 FLEX DUCT	103 STATIC PRESSURE SWITCH		
AO ANALOG OUTPUT	PV POST INDICATOR VALVE	105 BALANCING VALVE	TURNING VANES	104 TEMPERATURE SENSOR WITH AVERAGING ELEMENT	FIRE SUPPRESSION	
AP0 AIR PRESSURE DROP	PVC POLY VINYL CHLORIDE	106 CHECK VALVE	POSITIVE PRESSURE DUCT UP	105 MOTORIZED DAMPER		
AV ACID VENT	RA RETURN AIR	107 VACUUM BREAKER BACKFLOW VALVE 0.5- 2"	POSITIVE PRESSURE DUCT DOWN	106 SMOKE DAMPER	FIRE SUPPRESSION	
AW ACID WASTE	PW PURE WATER	108 PRESSURE REGULATING VALVE	NEGATIVE PRESSURE DUCT UP	107 STATIC PRESSURE SENSOR		
BFP BACK FLOW PREVENTER	RCP REINFORCED CONCRETE PIPE	109 STRAINER	NEGATIVE PRESSURE DUCT DOWN	108 MOTOR	FIRE SUPPRESSION	
BHP BRAKE HORSEPOWER	REL A RELIEF AIR	110 TEMPERATURE GAUGE 3.5" STEM	OVAL DUCT UP AND DOWN	109 VARIABLE FREQUENCY DRIVE		
BTU BRITISH THERMAL UNIT	RG REFRIGERANT HOT GAS	111 PRESSURE GAGE	MANUAL BALANCING DAMPER	110 TEMPERATURE SENSOR/THERMOSTAT	FIRE SUPPRESSION	
CA COMBUSTION AIR	RL REFRIGERANT LIQUID	112 MOTOR CONTROL VALVE	WALL LOUVER - EQUIP. MARK, SIZE	111 HUMIDITY SENSOR/HUMIDISTAT		
CD CONDENSATE DRAIN	RS REFRIGERANT SUCTION	113 STEAM TRAP - INVERTED BUCKET	MOTORIZED DAMPER - BLADES PARALLEL TO PAGE	112 CARBON DIOXIDE SENSOR	FIRE SUPPRESSION	
CHWR CHILLED OR HOT WATER RETURN	S SA SUPPLY AIR	114 GLOBE VALVE	PARALLEL OR OPPOSED BLADE MOTORIZED DAMPER	113 SENSOR		
CHWS CHILLED OR HOT WATER SUPPLY	SAN SANITARY WASTE PIPING (OUTSIDE BUILDING)	115 SOLENOID VALVE	BLADES PERPENDICULAR TO PAGE	114 SMOKE DETECTOR	FIRE SUPPRESSION	
CJ CAST IRON	SD SMOKE DAMPER	116 BASKET STRAINER	FIRE DAMPER AND ACCESS DOOR - EQUIP. MARK	115 DAMPER END SWITCH		
CO CLEAN OUT	SP STATIC PRESSURE	117 SANITARY/STORM DRAIN BELOW GRADE OR BELOW FLOOR	SMOKE DAMPER AND ACCESS DOOR - EQUIP. MARK	116 MOTORIZED DAMPER	FIRE SUPPRESSION	
CPD CONDENSATE PUMP DISCHARGE	SP SUMP PUMP	118 PIPING - SEE ABBREVIATION LEGEND FOR TYPE OF SERVICE. (E.G., CWS - SHALL BE CHILLED WATER SUPPLY)	COMBINATION FIRE/SMOKE DAMPER AND ACCESS DOOR - EQUIP. MARK	117 HUMIDIFIER		
CPVC CHLORINATED POLY VINYL CHLORIDE	SS SUB SOIL DRAIN	119 HOSE BIBB - EQUIP. MARK	CEILING DIFFUSER - EQUIPMENT MARK, SIZE, CFM	118 PIPING TEMPERATURE SENSOR	FIRE SUPPRESSION	
CR CONDENSER WATER RETURN	TAB TEST, ADJUST AND BALANCE	120 WALL HYDRANT - EQUIP. MARK (NON FREEZE TYPE)	SIDEWALL REGISTER - EQUIP. MARK, SIZE, CFM, HEIGHT AFF	119 PIPING THERMOMETER		
CS CONDENSER WATER SUPPLY	TC TEMPERATURE CONTROL CONTRACTOR	121 VENT THRU ROOF - MARK	CEILING RETURN GRILLE - EQUIP. MARK, SIZE, CFM	120 PIPING PRESSURE GAUGE	FIRE SUPPRESSION	
CW DOMESTIC COLD WATER	TD TRANSFER DUCT	122 FLOOR DRAIN, SIZE, EQUIP. MARK	ROOF DRAIN, SIZE, EQUIP. MARK	121 PIPING DIFFERENTIAL PRESSURE SENSOR		
CWR CHILLED WATER RETURN	TOD TOP OF DUCT	123 FLOOR SINK, SIZE, EQUIP. MARK	ROOF OVERFLOW DRAIN, SIZE, EQUIP. MARK	122 PIPING FLOW METER	FIRE SUPPRESSION	
CWS CHILLED WATER SUPPLY	TSP TOTAL STATIC PRESSURE	124 ROOF DRAIN, SIZE, EQUIP. MARK	SHOWER HEAD - EQUIP. MARK	123 PIPING TWO-WAY CONTROL VALVE		
DB DRY BULB	TW DOMESTIC TEMPERED WATER	125 SHOWER HEAD - EQUIP. MARK	CLEAN OUT	124 PIPING THREE-WAY CONTROL VALVE	FIRE SUPPRESSION	
DCI DUCTILE CAST IRON	TWC DOMESTIC TEMPERED WATER CIRCULATING	126 CLEAN OUT	FLOOR CLEAN OUT	125 CONNECTION - NEW TO EXISTING		
DI DIGITAL INPUT	V VENT	127 CLEAN OUT AT BASE OF STACK	GRADE CLEAN OUT	126 PIPE OR ROUND DUCT RISER	FIRE SUPPRESSION	
DO DIGITAL OUTPUT	VTR VENT THROUGH ROOF	128 CLEAN OUT AT BASE OF STACK	CLEAN OUT AT BASE OF STACK	127 PIPE OR ROUND DUCT DROP		
EAT ENTERING AIR TEMPERATURE	VUF VENT UNDER FLOOR	129 PANEL RADIATOR - EQUIP. MARK, LENGTH, GALLONS PER MINUTE	PANEL RADIATOR - EQUIP. MARK, LENGTH, GALLONS PER MINUTE	128 DIRECTION OF FLOW	FIRE SUPPRESSION	
EC ELECTRICAL CONTRACTOR	W SANITARY WASTE PIPING (INSIDE BUILDING)	130 ELBOW DOWN	ELBOW DOWN	129 DOWNWARD PIPE OR DUCT PITCH		
EMCS ENERGY MANAGEMENT AND CONTROL SYSTEM	W WATER SERVICE PIPING (OUTSIDE BUILDING)	131 ELBOW UP	ELBOW UP	130 SECTION IDENTIFICATION	FIRE SUPPRESSION	
ESP EXTERNAL STATIC PRESSURE	WB WET BULB	132 TEE DOWN	TEE DOWN	131 DETAIL IDENTIFICATION		
EWT ENTERING WATER TEMPERATURE	WCO WALL CLEAN OUT	133 TEE UP	TEE UP	132 ELECTRICAL MOTOR	FIRE SUPPRESSION	
F FIRE SUPPRESSION PIPING	WP0 WATER PRESSURE DROP	134 VARIABLE AIR VOLUME BOX WITH REHEAT - EQUIP. MARK, FLOW RATE	VARIABLE AIR VOLUME BOX WITH REHEAT - EQUIP. MARK, FLOW RATE	133 ARCHITECTURAL ELEVATION		
FCO FLOOR CLEAN OUT	XE RELOCATED EQUIPMENT, DEVICE, ETC.	135 VARIABLE AIR VOLUME BOX	VARIABLE AIR VOLUME BOX	134 ENGINEER ELEVATION	FIRE SUPPRESSION	
FD FLOOR DRAIN	XFR TRANSFER	136 REHEAT COIL	REHEAT COIL	135 ELECTRICAL PANEL		
FEA FUME HOOD EXHAUST AIR	XN NEW EQUIPMENT, DEVICE, ETC.			136 VARIABLE FREQUENCY DRIVE PANEL - EQUIP. MARK	FIRE SUPPRESSION	
FI FIRE HYDRANT	XR EXISTING CONDITION TO BE REMOVED OR RELOCATED			137 EXISTING PIPING, DUCTWORK, EQUIPMENT, ETC.		
FL FLOW LINE	XX-1 EQUIPMENT SCHEDULES (E.G., AHJ-1 - AIR HANDLING UNIT)				FIRE SUPPRESSION	
FOR FUEL OIL RETURN	VB VARIABLE AIR VOLUME BOX					
FOS FUEL OIL SUPPLY	VBR VARIABLE AIR VOLUME BOX WITH REHEAT				FIRE SUPPRESSION	
FV FUEL OIL VENT	VBF FAN POWERED VARIABLE AIR VOLUME BOX					
FSD FIRE/SMOKE DAMPER	VBRF FAN POWERED VARIABLE AIR VOLUME BOX WITH REHEAT				FIRE SUPPRESSION	
G GAS						
GBD GRAVITY BACKDRAFT DAMPER					FIRE SUPPRESSION	
GC GENERAL CONTRACTOR						
GCO GRADE CLEANOUT					FIRE SUPPRESSION	
GEA GENERAL EXHAUST AIR						
GPM GALLONS PER MINUTE					FIRE SUPPRESSION	
HP HORSEPOWER						
HPR HIGH PRESSURE STEAM RETURN					FIRE SUPPRESSION	
HPS HIGH PRESSURE STEAM SUPPLY						
HR HOUR					FIRE SUPPRESSION	
HW DOMESTIC HOT WATER						
HW 180 DOMESTIC HOT WATER 180 DEG. F. SERVICE					FIRE SUPPRESSION	
HW 180 DOMESTIC HOT WATER CIRCULATION 180 DEG. F. SERVICE						
HWR HOT WATER RETURN					FIRE SUPPRESSION	
HWS HOT WATER SUPPLY						
IE INVERT ELEVATION					FIRE SUPPRESSION	
KEA KITCHEN EXHAUST AIR						
KS KITCHEN SUPPLIER					FIRE SUPPRESSION	
KW KILOWATT						
LA LABORATORY AIR					FIRE SUPPRESSION	
LAT LEAVING AIR TEMPERATURE						
LIT LAY IN TILE					FIRE SUPPRESSION	
LCW LABORATORY COLD WATER						
LFC LOOP FIELD CONTRACTOR					FIRE SUPPRESSION	
LFD LOOP FIELD DRAIN						
LFS LOOP FIELD SUPPLY					FIRE SUPPRESSION	
LG LABORATORY GAS						
LHW LABORATORY HOT WATER					FIRE SUPPRESSION	
LHWC LABORATORY HOT WATER RECIRC						
LPR LOW PRESSURE STEAM SUPPLY					FIRE SUPPRESSION	
LPS LOW PRESSURE STEAM RETURN						
LV LABORATORY VACUUM					FIRE SUPPRESSION	
LWT LEAVING WATER TEMPERATURE						
MA MIXED AIR					FIRE SUPPRESSION	
MB MIXING BOX						
MBH 1000 BTUHR					FIRE SUPPRESSION	
MC MECHANICAL CONTRACTOR						
MCC MOTOR CONTROL CENTER					FIRE SUPPRESSION	
MD MOTORIZED DAMPER						
MH MAN HOLE					FIRE SUPPRESSION	
MPS MEDIUM PRESSURE STEAM RETURN						
MPS MEDIUM PRESSURE STEAM SUPPLY					FIRE SUPPRESSION	
NC NOISE CRITERIA						
NIC NOT IN CONTRACT					FIRE SUPPRESSION	

GENERAL MECHANICAL NOTES:

1. GENERAL

- THESE NOTES SHALL APPLY TO ALL MECHANICAL PLANS.
- NOTE THAT THE MECHANICAL PLANS ARE TO A GREAT EXTENT SCHEMATIC IN NATURE AND THAT THE INFORMATION PRESENTED IS EXACT AS COULD BE SECURED. THE CONTRACTOR SHALL OBTAIN EXACT LOCATIONS, MEASUREMENTS, LEVELS, ETC., AT THE SITE AND SHALL SATISFACTORILY ADAPT HIS WORK TO THE ACTUAL CONDITIONS AT THE PROJECT SITE.
- THE CONTRACTOR IS RESPONSIBLE FOR PROPER SUPPORT OF ALL EQUIPMENT, PIPING, DUCTWORK, ETC. COORDINATE INSTALLATION OF ALL EQUIPMENT, PIPING, DUCTWORK, ETC. WITH OTHER BUILDING TRADES.
- SEE SPECIFICATION SECTIONS 22 05 00 AND 23 05 00 FOR OTHER GENERAL MECHANICAL REQUIREMENTS.
- THE LOCATION AND SIZE OF ALL ITEMS SHOWN AS EXISTING WERE OBTAINED FROM PREVIOUS DRAWINGS AND SITE VISITS, AND ARE SHOWN FOR THE CONVENIENCE OF THE CONTRACTOR. ACCURACY OF THE INFORMATION SHOWN IS NOT GUARANTEED. THE CONTRACTOR IS RESPONSIBLE FOR THE VERIFICATION OF ALL EXISTING CONDITIONS PRIOR TO SUBMITTING THE PROJECT BID. NO ADDITIONAL COMPENSATION WILL BE ALLOWED FOR CHANGES WHICH OCCUR AFTER BIDS ARE SUBMITTED WHICH ARE A RESULT OF EXISTING CONDITIONS. SITE VISITS PRIOR TO SUBMISSION OF BIDS MUST BE FULLY COORDINATED WITH THE OWNER.

- ALL EXPOSED MECHANICAL ITEMS WILL BE FIELD-PAINTED. ALL ITEMS SHALL BE PROPERLY ORDERED AND PREPARED TO ACCEPT PAINT. COORDINATE EXACT REQUIREMENTS WITH PAINTING CONTRACTOR. SEE ARCHITECTURAL AND FINISH DRAWINGS AND SPECIFICATIONS FOR AREAS AND ITEMS THAT WILL BE PAINTED.

- CONTRACTOR SHALL INCLUDE DEMOLITION OF ALL EXISTING CONTROL SYSTEMS FOR ALL ITEMS/EQUIPMENT SHOWN ON PLANS AS BEING REMOVED.
- THE CONTRACTOR SHALL COORDINATE THE REMOVAL OF ANY SYSTEM CONTAINING REFRIGERANT WITH THE OWNER'S REPRESENTATIVE PRIOR TO REMOVAL. THE OWNER WILL RECOVER REFRIGERANT FROM SYSTEMS PRIOR TO REMOVAL BY CONTRACTOR. NOTIFY OWNER A MINIMUM OF SEVEN (7) DAYS PRIOR TO REMOVAL OF SYSTEM.

- ALL ACCESS PANELS/LOCATIONS SHALL BE COORDINATED WITH THE OWNER PRIOR TO FINAL INSTALLATION. ENSURE FINAL INSTALLATION. LOCATION PROVIDES REQUIRED ACCESS TO ALL MECHANICAL EQUIPMENT AND ASSOCIATED COMPONENTS.

SITE UTILITIES

- ALL CONNECTIONS TO UTILITY MAINS SHALL BE COORDINATED WITH THE OWNER'S REPRESENTATIVE VIA WRITTEN NOTICE GIVEN A MINIMUM OF SEVEN DAYS PRIOR TO WORK.

DUCTWORK

- ALL DUCT DIMENSIONS CALLED OUT ARE INTERIOR AIR FLOW DIMENSIONS. UNLESS OTHERWISE NOTED, ALL SUPPLY, RETURN, EXHAUST, OUTSIDE AND RELIEF AIR DUCT IS GALVANIZED STEEL. UNLESS OTHERWISE NOTED, ALL SUPPLY DUCT MITERED ELBOWS SHALL BE INSTALLED WITH TURNING VANES. ALL ROUND ELBOWS SHALL BE FULL-RADIUS TYPE. ALL ROUND-TO-RECTANGULAR BRANCH CONNECTIONS SHALL BE 45-DEGREE ENTRY. LOW-LOSS FITTINGS. ALL CANOPY HOOD EXHAUST DUCTWORK SHALL BE STAINLESS STEEL AND IS SHOWN ON THE DRAWINGS AS SHADED.
- ALL SUPPLY AIR DUCT SHALL BE WRAPPED WITH INSULATION UNLESS OTHERWISE NOTED OR SPECIFIED. EXHAUST AIR DUCT SHALL BE LEFT UNINSULATED UNLESS LINER IS EXPLICITLY CALLED OUT.
- ALL EXPOSED DUCTWORK SHALL BE INSTALLED IN A NEAT AND WORKMAN-LIKE MANNER FREE FROM ALL VISIBLE DENTS AND KINKS. DUCT RUNS SHALL BE STRAIGHT AND LEVEL.

PIPING

- UNLESS OTHERWISE NOTED, MINIMUM HEATING HOT WATER SUPPLY/RETURN RUN-OUTS TO EQUIPMENT SHALL BE 3/4" SIZE.
- SEE PLUMBING FIXTURE CONNECTION SCHEDULE FOR PIPE SIZES REQUIRED AT FIXTURES. PROVIDE WATER HAMMER ARRESTORS AT COLD WATER BRANCHES AS REQUIRED BY PDH-W021. PROVIDE ACCESS TO EACH WATER HAMMER ARRESTOR.
- UNLESS NOTED OTHERWISE, WASTE AND STORM DRAINAGE PIPING HAS BEEN DESIGNED TO ACCOMMODATE A SLOPE OF 1/8" PER LINEAR FOOT FOR PIPING GREATER THAN 3" IN DIAMETER AND A SLOPE OF 1/4" PER LINEAR FOOT FOR 3" AND SMALLER DIAMETER PIPE.
- PIPE HANGERS SUSPENDED FROM STRUCTURAL FLOOR OR ROOF JOIST AND SUPPORTING MORE THAN 200 LBS SHALL BE ATTACHED TO THE TOP MEMBER OF THE JOIST.
- INSTALL MANUAL AIR VENTS AT ALL HIGH POINTS IN PIPING SYSTEMS, INCLUDING ALL SUPPLY AND RETURN SYSTEMS. INSTALL AUTOMATIC AIR VENT AT THE HIGHEST POINT IN EACH SYSTEM WITH MANUAL SHUT-OFF BALL VALVE.

TEMPERATURE CONTROLS

- ALL EXACT SENSOR, CONTROL PANEL AND THERMOSTAT LOCATIONS SHALL BE COORDINATED WITH THE ENGINEER.
- UNLESS OTHERWISE NOTED, ALL AIR TERMINAL UNITS, CABINET UNIT HEATERS, UNIT HEATERS, ETC. SHALL BE PROVIDED WITH A THERMOSTAT OR CONTROL DEVICE REGARDLESS OF WHETHER ONE IS SHOWN ON THE PLANS.
- UNLESS OTHERWISE NOTED, ALL THERMOSTATS SHALL BE WALL MOUNTED AT 48" A.F.F.




SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schimmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Mechanical Abbreviations,
Symbols & Notes


M0.00



1 DUCT TRANSITION DETAILS
NO SCALE




2 DUCT ELBOW DETAILS
NO SCALE




3 REMOTE DAMPER OPERATOR DETAIL
NO SCALE

- GENERAL NOTE:
- WHERE SHOWN ON PLAN WHEN THERE ARE MULTIPLE REMOTE DAMPERS CO-LOCATED. ROUTE THEIR CABLE TO A SINGLE COMMON LOCATION. POSSIBLE LOCATION CAN BE RETURN GRILLE, LIGHT FIXTURE, ACCESS PANEL, REMOVABLE CEILING TILE, ETC.




4 DUCTWORK T-JUNCTION DETAIL
NO SCALE
NOTE: DETAIL APPLIES TO ALL DUCTWORK IN WHICH AIRFLOW SPLITS IN 2 DIRECTIONS. REFER TO OTHER DETAILS FOR BRANCH TAKE-OFFS.




- NOTES:
- ALL FLOOR-MOUNTED EQUIPMENT SHALL BE PROVIDED WITH AN EQUIPMENT PAD.
 - FLOOR UNDER BASE PAD SHALL BE ROUGHENED AND BASE SHALL BE DOWELED TO FLOOR. ADJUST BASE SIZE AS REQUIRED FOR INDIVIDUAL EQUIPMENT INSTALLED.
 - ALL EQUIPMENT PADS THAT SUPPORT BOTH EQUIPMENT AND INERTIA BASES SHALL BE REINFORCED WITH #6 REBAR INSTALLED AT 12\"/>

5 EQUIPMENT PAD DETAIL
NO SCALE



6 LOUVER DETAIL
NO SCALE
GENERAL NOTE:
1. PROVIDE INSULATED BLANK OFF PANEL WHERE DUCTWORK IS NOT ATTACHED.



7 DUCT TAKE-OFF DETAILS
NO SCALE


 **SHEET HISTORY:**
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary

Mechanical Details

M2.01

Plot Time Stamp: 5/15/2023 10:06:12 AM
File Location/Name: C:\11 Revit Projects\2022\508020-SWSWB-M22_erc.nsklon@clarkensersen.com.rvt

LOUVER SCHEDULE

MARK	OPERATING CONDITIONS	SIZE	TOTAL FACE AREA	CFM	VELOCITY FPM	APD	MINIMUM FREE AREA SQ.FT	CONSTRUCTION MATERIAL	BLADE SPACING/ANGLE	SCREEN	FINISH	MANUFACTURER OR APPROVED EQUIVALENT	MODEL	REMARKS
L-1	EXHAUST AIR	36"x12"	3 SQUARE FEET	1,150	681	0.17	1.0	6063 EXTRUDED ALUMINUM	4.75"HORIZONTAL	BIRD	BAKED ENAMEL	RUSKIN	EME22000	1,2,3,4
L-2	OUTSIDE AIR	36"x12"	3 SQUARE FEET	1,200	681	0.17	1.0	6063 EXTRUDED ALUMINUM	4.75"HORIZONTAL	BIRD	BAKED ENAMEL	RUSKIN	EME22000	1,2,3,4

REMARKS:
1. PROVIDE COLOR CHART AT SHOP DRAWING REVIEW FOR COLOR.
FINAL COLOR TO BE SELECTED BY ARCHITECT FROM MANUFACTURER'S FULL RANGE OF COLORS (2 AND 3 COAT COLORS)
2. PROVIDE GALVANIZED BIRDSCREEN, 0.5" MESH TYPE
3. PROVIDE ALUMINUM INSECT SCREEN
4. COORDINATE FRAME WITH EXTERIOR MOUNTING CONDITIONS

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.

HEAT PUMP SCHEDULE

MARK	MANUFACTURER	MODEL	COOLING PERFORMANCE						HEATING PERFORMANCE				
			CAPACITY	SENSIBLE	LATENT	SUPPLY AIR	OUTDOOR DB	ENTERING DB	ENTERING WB	LEAVING DB	LEAVING WB	HEAT PUMP CAPACITY	POWER SUPPLY
HP-1	CARRIER	GHESSAN43600A	34,200	26,403	8,347	1127	95 F	80 F	67 F	60.7 F	58 F	17 F - 20,400 BTUH	208/160
HP-2	CARRIER	GHESSAN43600A	34,200	26,403	8,347	1127	95 F	80 F	67 F	60.7 F	58 F	17 F - 20,400 BTUH	208/160
HP-3	CARRIER	GHESSAN43600A	34,200	26,403	8,347	1127	95 F	80 F	67 F	60.7 F	58 F	17 F - 20,400 BTUH	208/160

REMARKS:
1. PROVIDE SINGLE POINT ELECTRICAL CONNECTION
2. PROVIDE R-410A REFRIGERANT CHARGE
3. PROVIDE ALL REQUIRED INSULATED REFRIGERANT LINES
4. PROVIDE ALL STANDARD FIVE (5) YEAR COMPRESSOR WARRANTY
5. PROVIDE SPECIALTIES FOR A COMPLETE AND OPERATIONAL SYSTEM
6. AMBIENT AIR TEMPERATURE FOR ALL UNITS 95 DEF F.

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.

EXHAUST FAN SCHEDULE

		FAN PERFORMANCE DATA				MOTOR DATA				ELECTRICAL DATA				MANUFACTURER OR EQUIVALENT		MODEL	REMARKS
MARK	SERVES	PRIMARY EXHAUST (CFM)	INLET E.S.P. (IN. W.G.)	FAN RPM	FAN DISCHARGE	IMPELLER DRIVE	MOTOR HP	BRAKE HP	MOTOR FLA (AMPS)	VOLTS	PHASE	HZ					
EF-1	MENS	575	.5	1686	7/8" INE	DIRECT	1/6	12	2.8	115	1	60	GREENHECK		SQ-95-VG	1	
EF-2	WOMANS	575	.5	1686	IN LINE	DIRECT	1/6	12	2.8	115	1	60	GREENHECK		SQ-95-VG	1	

REMARKS:

1. PROVIDE WITH VAR-GRN ECM MOTOR CONTROL - DIAL ON FAN HOUSING. DISCONNECT SWITCH, THERMAL OVERLOAD PROTECTION, GRAVITY DAMPER, INSULATED HOUSING (1"), VIBRATION ISOLATORS AND BRACKETS, FLEXIBLE DUCT CONNECTIONS, AND WIRING PIGTAIL.

NOTE:

THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".

BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.

DIFFUSER, REGISTER AND GRILLE SCHEDULE

MARK	TYPE	MAX. P.D. (IN. WG.)	MAX. N.C.	MAXIMUM CFM	MANUFACTURER AND MODEL NUMBER	REMARKS
R-1	REGISTER	0.15	20	SEE PLANS FOR CFM AND SIZE	TITUS 350FSF1 OR EQUIVALENT	3/4" BLADE SPACING, FIXED SINGLE DEFLECTION AT 35 DEGREE ANGLE. BLADES PARALLEL TO LONG DIMENSION. ALUMINUM FRAME AND BLADES, CONCEALED SCREW MOUNTING, WHITE FINISH, COORDINATE WITH CEILING / WALL TYPE. BOTTOM HINGE, QUARTER-TURN FASTENER, 1" FILTER SLOT.
R-2	REGISTER	-0.1	20	SEE PLANS FOR CFM AND SIZE	TITUS 350FLF1 OR EQUIVALENT	3/4" BLADE SPACING, FIXED SINGLE DEFLECTION AT 35 DEGREE ANGLE. BLADES PARALLEL TO LONG DIMENSION. ALUMINUM FRAME AND BLADES, CONCEALED SCREW MOUNTING, WHITE FINISH, COORDINATE WITH CEILING / WALL TYPE. PRIOR TO ORDERING CONFIRM MANUFACTURER RECOMMENDED INSTALLATION.
R-3	REGISTER	-0.1	20	SEE PLANS FOR CFM AND SIZE	TITUS 33RL OR EQUIVALENT	1/2" BLADE SPACING, FIXED SINGLE DEFLECTION AT 38 DEGREE ANGLE. BLADES PARALLEL TO LONG DIMENSION, HEAVY DUTY STEEL, 16 GAUGE BORDER AND 14 GAUGE BLADES, CONCEALED SCREW MOUNTING, WHITE FINISH, COORDINATE WITH WALL TYPE.
DL-1	DRUM LOUVER	0.15	20	SEE PLANS FOR CFM AND SIZE	TITUS DL-SV OR EQUIVALENT	ADJUSTABLE HORIZONTAL AND VERTICAL THROW, SPLIT VANES. ALUMINUM DRUM, COORDINATE WITH WALL TYPE. PRIOR TO ORDERING CONFIRM MANUFACTURER RECOMMENDED INSTALLATION.

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.

HEATER SCHEDULE

MARK	MANUFACTURER OR EQUIVALENT	MODEL	WATTS	BTU PER HR.	CFM	MIN. OLT AMPS HEATER AMPS	ELECTRICAL	MAX. THROW
EH-1	QMARK	MYUHS004	2500	8533	270	10.4 13	240/160	16 FT
EH-2	QMARK	MYUHS004	2500	8533	270	10.4 13	240/160	16 FT

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.

FAN COIL SCHEDULE

MARK	MANUFACTURER	MODEL	CFM	PRESSURE	BLOWER TYPE	CIRCUIT 1 MOC	CIRCUIT 2 MOC	ELECTRIC HEAT	POWER SUPPLY
FC-1	CARRIER	FJ4DNX38L00	1127.0	.5 IN WG	DIRECT DRIVE	60	50	20 KW	240/160
FC-2	CARRIER	FJ4DNX38L00	1127.0	.5 IN WG	DIRECT DRIVE	60	50	20 KW	240/160
FC-3	CARRIER	FJ4DNX38L00	1127.0	.5 IN WG	DIRECT DRIVE	60	50	20 KW	240/160

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Mechanical Schedules

M3.01

Plot Time Stamp: 5/15/2023 10:06:13 AM
File Location/Name: C:\11 Revit Projects\2022\508020-SWSWB-W22_erc.nsklon@clarkensers.com.rvt



BELOW FLOOR PLUMBING PLAN
SCALE: 1/4" = 1'-0"


SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Below Floor Plumbing
Plan

P1.01

Plot Time Stamp: 5/15/2023 10:00:15 AM
File Location/Name: C:\11 Revit Projects\2022\508020-SBSWB-W22_e.rvt



FIRST FLOOR PLUMBING PLAN
SCALE: 1/4" = 1'-0"


SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

First Floor Plumbing Plan


P1.02




1 AHU (BLOW-THROUGH TYPE) CONDENSATE DRAIN TRAP DETAIL
NO SCALE
NOTE: H = FAN OUTLET PRESSURE + 1". VERIFY VALUE WITH MANUFACTURER.



2 WALL HYDRANT DETAIL
NO SCALE



3 TYPICAL PIPE HANGER DETAIL
NO SCALE



4 DOMESTIC WATER TREATMENT PIPING SCHEMATIC
SCALE: NO SCALE




SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Plumbing Details

P2.01



WASTE & VENT RISER DIAGRAM
NO SCALE



DOMESTIC WATER RISER DIAGRAM
NO SCALE




SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary

Riser Diagrams

P3.01

WATER SOFTENER SCHEDULE

MARK	SERVICES	TYPE	DWT	OPERATING CONDITIONS				EQUIPMENT SIZE			EXCHANGE CAPACITY KILOGRAMS @ LB SALT	ELECTRICAL DATA			MANUFACTURER OR APPROVED EQUIVALENT	MODEL	REMARKS
				PEAK FLOW GPM	WPD	CONT. FLOW GPM	WPD	RESIN FT ³	SOFTENER TANK	BRINE TANK		VOLTS	PHASE	HZ			
WS-1A	DOMESTIC HOT WATER	DUPLEX	40 F	60	25 PSI	40	15 PSI	15	31'x31"	31'x48"	375/10	120	1	60		1500	1,2,3,4,5,6,7,8,9
WS-1B	DOMESTIC HOT WATER	DUPLEX	40 F	60	25 PSI	40	15 PSI	15	31'x31"	31'x48"	375/10	120	1	60		1500	1,2,3,4,5,6,7,8,9

REMARKS:
1. TANK CONSTRUCTION SHALL BE REINFORCED POLYESTER.
2. PROVIDE A POLYETHYLENE BRINE TANK.
3. PROVIDE WITH A FULLY INTEGRATED PROGRAMMABLE MICROPROCESSOR DRIVEN ELECTRONIC CONTROLLER TO AUTOMATICALLY CYCLE THE MAIN OPERATING VALVE THROUGH THE REGENERATION SEQUENCE.
4. 100 PSI RATED.
5. WATER SOFTENER SHALL BE INSTALLED AND SET UP BY EQUIPMENT SUPPLIER PER MANUFACTURER RECOMMENDATIONS.
6. DUPLEX PROGRESSIVE WATER METER REQUIRED.
7. 1344-SS RETENTION TANK 13"x44" 1-1/2" CONNECTIONS, 66 GPM FLOW RATE.
8. 02111062 STENNER ECON PUMP & 15 GALLON TANK ASSEMBLY.
9. ALL CHEMICAL FEEDERS MUST HAVE PRIMARY AND SECONDARY INTERCONNECT CONTROL DEVICES TO PREVENT OVER FEEDING. WHERE APPLICABLE, CHEMICAL FEEDERS MUST BE ELECTRICALLY INTERCONNECTED WITH THE WELL PUMP AND ALSO BE PROVIDED WITH SECONDARY CONTROL DEVICES.

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.

PLUMBING FIXTURE AND EQUIPMENT CONNECTION SCHEDULE

MARK	FUNCTION		MANUFACTURER AND MODEL	WASTE	VENT	HW	SCW
L-1	FOUR STATION LAVATORY	LAVATORY:	SLOAN MODEL DSWD-8000 OR APPROVED EQUIVALENT SOLID SURFACE FOUR STATION WEIR DECK WITH TWO DRAINS AND FOUR SETS OF FAUCET HOLES. TOTAL LENGTH TO BE 10'-0". COLOR TO BE DUPONT CORIAN SILVER BIRCH.	2"	1-1/2"	1/2"	1/2"
		FAUCET (FOUR):	SLOAN MODEL EPX-600-202-0010, OR APPROVED EQUIVALENT, LINE POWERED SENSOR OPERATED WITH BATTERY BACKUP. BELOW DECK MIXING VALVE, 1.5 GPM SPRAY HEAD.				
		TRAP (TWO):	MINIMUM 17 GAUGE CHROME PLATED CAST BODY WITH ESCUTCHEON.				
		DRAIN (TWO):	CHROME PLATED GRID DRAIN.				
		SUPPLIES (FOUR SETS):	LEAD FREE CHROME PLATED LOOSE KEYSTOP VALVES WITH DEEP ESCUTCHEON PLATES.				
		REMARKS:	SEE NOTE #2.				
L-2	COUNTERTOP LAVATORY	LAVATORY:	SOLID SURFACE COUNTERTOP WITH INTEGRAL SINK BASIN BY THE GENERAL CONTRACTOR.	2"	1-1/2"	1/2"	1/2"
		FAUCET:	SLOAN MODEL EPX-600-202-0010, OR APPROVED EQUIVALENT, LINE POWERED SENSOR OPERATED WITH BATTERY BACKUP. BELOW DECK MIXING VALVE, 1.5 GPM SPRAY HEAD.				
		TRAP:	MINIMUM 17 GAUGE CHROME PLATED CAST BODY WITH ESCUTCHEON.				
		DRAIN:	CHROME PLATED GRID DRAIN.				
		SUPPLIES:	LEAD FREE CHROME PLATED LOOSE KEYSTOP VALVES WITH DEEP ESCUTCHEON PLATES.				
		REMARKS:	SEE NOTE #2.				
HJUR-1	URINAL (HANDICAPPED)	FIXTURE:	KOHLER MODEL K-4891-ERS8 BAROON OR EQUIVALENT, WHITE VITREOUS CHINA, INTEGRAL TRAP, 3/4" REAR SPUD, ELONGATED LIP, 1 GAL PER FLUSH.	2"	1-1/2"		3/4"
		VALVE:	SLOAN ROYAL MODEL 195-1 ES-8 TWO OR APPROVED EQUIVALENT CONCEALED DIAPHRAGM HARD WIRED SENSOR OPERATED WITH HYDRAULIC METAL PUSH BUTTON ASSEMBLY FOR TRUE MECHANICAL NON HOLD OPEN OVERRIDE.				
		CARRIER:	CONCEALED WALL CARRIER.				
HJWC-1	WATER CLOSET (HANDICAPPED)	FIXTURE:	KOHLER MODEL K-4323 KINGSTON OR EQUIVALENT, 1.6 GAL PER FLUSH, WHITE VITREOUS CHINA, WALL MOUNTED, SIPHON JET WITH 1-1/2" REAR SPUD.	4"	2"		1"
		VALVE:	SLOAN ROYAL MODEL 140-1.6 ES-8 TWO OR APPROVED EQUIVALENT CONCEALED DIAPHRAGM HARD WIRED SENSOR OPERATED WITH HYDRAULIC METAL PUSH BUTTON ASSEMBLY FOR TRUE MECHANICAL NON HOLD OPEN OVERRIDE.				
		SEAT:	WHITE, OPEN FRONT, HEAVY DUTY COMMERCIAL GRADE, NO LID ON SEAT.				
		CARRIER:	WALL HUNG, CONCEALED WALL CARRIER.				
HEWC-1	ELECTRIC WATER COOLER	COOLER:	ELKAY MODEL EZSLR8WS OR EQUIVALENT, B.LEVEL PUSH BAR OPERATION, STAINLESS STEEL FINISH, 8 GPH @ 50 DEG. F WATER CAPACITY WITH BOTTLE FILLING STATION. 18 HP COMPRESSOR MOTOR. FIVE YEAR COMPRESSOR WARRANTY 120 VOLT, 1 PHASE, 60 HERTZ.	1-1/2"	1-1/2"		1/2"
MSB-1	MOP SERVICE BASIN	SINK:	FIAT MODEL MSB-2424 OR EQUIVALENT, MOLDED STONE, 24" X 24" X 10" SIZE. PROVIDE COMBINATION DOME STRAINER WITH LINT BASKET, DRAIN BODY. PROVIDE MOP & HOSE HANGER.	3"	1-1/2"	1/2"	1/2"
		FAUCET:	KOHLER MODEL K-8804 OR EQUIVALENT CHROME PLATED WITH VACUUM BREAKER SPOUT WITH PAL HOOK AND WALL SUPPORT.				
FS-1	FLOOR SINK	DRAIN:	JAY R. SMITH MODEL 3150Y OR EQUIVALENT. CAST IRON BODY WITH FLANGE, 8" DEEP ACID RESISTANT EPOXY INTERIOR. INTEGRAL CLAMPING COLLAR, SEEPAGE OPENING, 3/4 NICKLE BRONZE 12"x12" GRATE, DOME STRAINER, NO HUB CONNECTION.	(SEE PLANS)	(SEE PLANS) (SEE NOTE 1)		
FD-1	FLOOR DRAIN (FINISHED AREAS)	DRAIN:	JAY R. SMITH MODEL 208Y OR EQUIVALENT. CAST IRON BODY WITH FLANGE. INTEGRAL CLAMPING COLLAR, SEEPAGE OPENINGS, 9" DIAMETER SATIN NICKLE BRONZE STRAINER, NO HUB CONNECTION.	(SEE PLANS)	(SEE PLANS) (SEE NOTE 1)		
SD-1	SLOT DRAIN	DRAIN:	JOSAM MODEL 47122 OR APPROVED EQUIVALENT FABRICATED STAINLESS STEEL SLOT DRAIN. 5/16" SLOT WITH END RUN OUTLET. OUTLET DRAIN TO BE PROVIDED WITH VANDAL PROOF ANTI SLIP MESH GRATE. 2" OUTLET, SEE PLANS FOR LENGTH.	2"	(SEE PLANS) (SEE NOTE 1)		
HB-1	HOSE BIBB	BIBB:	WOODFORD MODEL 26, C INLET WALL FAUCET OR EQUIVALENT. ASSE 1052 APPROVED TWO CHECK BACKFLOW PREVENTER, BRASS FINISH, 3/4" HOSE CONNECTION, WHEEL OPERATION HANDLE.				3/4"
HB-2	HOSE SUPPLY BOX	BIBB:	ACORN MODEL 8151 OR EQUIVALENT SINGLE TEMPERATURE WITH VACUUM BREAKER RECESSED 18 GAUGE TYPE 304 STAINLESS STEEL BOX WITH FLANGE AND LOCKABLE DOOR.				3/4"
WH-1	WALL HYDRANT	HYDRANT:	WOODFORD MODEL 87 FROST PROOF AUTOMATIC DRAINING, BACKFLOW PREVENTER, FROST PROOF HYDRANT WITH ASSE 1052 APPROVED TWO CHECK BACK FLOW PREVENTER, CHROME FINISH, 3/4" HOSE CONNECTION STAINLESS STEEL STEM, LOOSE KEY OPERATING HANDLE, SEE NOTE 3.				3/4"
EWH-1	ELECTRIC WATER HEATER	HEATER:	A. O. SMITH MODEL DEN-52 OR EQUIVALENT, 52 GALLON STORAGE TANK, 15 GPH @ 80 DEG. F RISE, DUAL NON SIMULTANEOUS 3,000 WATT ELEMENTS, 208 VOLT / 1 PH / 60 HZ.			3/4"	3/4"
PVB-1	IRRIGATION PRESSURE VACUUM BREAKER	VACUUM BREAKER:	WATTS MODEL 800 OR EQUIVALENT BRONZE BODY VACUUM BREAKER. 2" CONNECTION SIZE, 50 GPM WATER FLOW RATE.				2"
RO-1	REVERSE OSMOSIS SYSTEM	REVERSE OSMOSIS:	REO-PURE MODEL L53-225 GPD OR APPROVED EQUIVALENT. 115 VOLT, 750 GALLON A DAY PRODUCTION. FULLY INTEGRATED RACK MOUNTED SYSTEM WITH TARGET TDS MONITORING. PROVIDE WITH DM-2A DIGITAL INLINE LCD DUAL METER FOR LPS RO, FLEXWAVE SSGD-35 STORAGE TANK AND AQUAJET VARIABLE SPEED PUMP 0.3 TO 4 GPM MODEL 5501-BND1773-5X, 12" ID.				1/2"
HWCP-1	HOT WATER CIRCULATING PUMP	PUMP:	BELL & GOSSETT MODEL E34V-BTXYZ OR EQUIVALENT. 3 GPM AT 4 FT OF HEAD, 10 WATTS, PRE-WIRED 8 FT ELECTRICAL PLUG, E3 TIMER.				

REFER TO ARCHITECTURAL INTERIOR ELEVATIONS FOR FIXTURE MOUNTING HEIGHTS OR MOUNT AT MANUFACTURERS RECOMMENDED HEIGHTS.

PLUMBING SCHEDULE NOTES:

1) MINIMUM SIZE OF UNDER SLAB VENT SHALL BE 2".

2) ALL HANDICAPPED LAVATORIES (HL-4) & ALL CL-1'S SHALL BE INSTALLED WITH P-TRAP AND SUPPLY INSULATION. PROVIDE TREBER MODEL #102 OR EQUAL WITH P-TRAP INSULATION, HOT AND COLD WATER ANGLE VALVE AND SUPPLY INSULATION FABRICATED FROM CLOSED CELL VINYL, 3/16" WALL THICKNESS, 74" VALUE OF 1.17 (BTU/IN²HR²FT²2"DEG F).

3) CONTRACTOR SHALL VERIFY ALL WALL THICKNESS AND SHALL ORDER APPROPRIATE OPERATING ROD ASSEMBLY.

4) SUPPLY STOPS MAY BE ELIMINATED AT THE CONTRACTORS OPTION WHEN PLUMBING FIXTURE IS LOCATED IN A CABINET. AND THE FIXTURE HAS SHUT-OFF VALVES TO ISOLATE THE FIXTURE FROM THE OTHER FIXTURES. ESCUTCHEONS MAY BE ELIMINATED WHERE THE SUPPLIES PENETRATE THE BOTTOM OF CASEWORK.

NOTE:
THE SCHEDULED PRODUCT IS SPECIFIED AS A BASIS OF DESIGN AND DOES NOT GUARANTEE IT COMPLIES WITH THE BUY AMERICA ACT AS STATED IN SPECIFICATION SECTION 01 20 00 "BUY AMERICA".
BASIS OF DESIGN PRODUCTS MUST BE VERIFIED AS BEING COMPLIANT WITH THE BUY AMERICA ACT IN ADDITION TO MEETING PERFORMANCE REQUIREMENTS AS SPECIFIED IN THIS SECTION AND ANY OTHER RELATED SECTIONS.



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A






May 15, 2023



Preliminary

Plumbing Schedules

P4.01





SHEET HISTORY:
 ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023




Preliminary

Mechanical Sections

PM1.01

Plot Time Stamp: 5/15/2023 10:00:18 AM
File Location/Name: C:\(1) Revit Projects\2022\508020-SRSWB-M22 eric.nelson@clarkensersen.com.rvt



FOOTING & FOUNDATION PLAN
SCALE: 1/4" = 1'-0"

GRADE BEAM SCHEDULE	
MARK	SIZE
1	8" WIDE x 3'-10" DEEP GRADE BEAM W/ (1) #5 TOP & BOTTOM & #4 VERT. @ 24" O.C.
2	1'-6" WIDE x 4'-6" DEEP GRADE BEAM W/ (3) #5s TOP & BOTTOM & #4 STIRRUPS @ 24" O.C.
3	4'-0" WIDE x 3'-10" DEEP GRADE BEAM W/ (4) #7s TOP & BOTTOM & #4 STIRRUPS @ 24" O.C.
4	5'-0" WIDE x 3'-10" DEEP GRADE BEAM W/ (5) #7s TOP & BOTTOM & #4 STIRRUPS @ 24" O.C.
5	5'-8" WIDE x 3'-10" DEEP GRADE BEAM W/ (6) #7s TOP & BOTTOM & #4 STIRRUPS @ 24" O.C.

GENERAL EARTH MOVING NOTES:

- SEE GEOTECHNICAL ENGINEERING REPORT PREPARED BY MID-STATE ENGINEERING & TESTING, DATED 05/04/2023, AND SPECIFICATIONS FOR EARTHWORK AND FOUNDATION PREPARATION REQUIREMENTS. ALL RECOMMENDATIONS GIVEN SHALL BE CONSIDERED PART OF THE CONSTRUCTION DOCUMENT SET.
- FILL MATERIAL. FILL MATERIAL SHALL CONSIST OF LEAN CLAYS OR CLAYEY SANDS WITH A MINIMUM OF 30% CLAYS / SILTS AS NOTED IN THE GEOTECHNICAL ENGINEERING REPORT.
- FILL SETTLEMENT. TIME SHALL BE ALLOWED FOR THE NEW FILL TO SETTLE AS NOTED IN THE GEOTECHNICAL ENGINEERING REPORT.

GENERAL FOUNDATION NOTES:

- THE GENERAL CONTRACTOR IS RESPONSIBLE FOR VERIFICATION AND COORDINATION OF ALL DIMENSIONS WITH THE MECHANICAL UNIT SUPPLIER.
- INDICATES TOP OF FOOTING ELEVATION.
- INDICATES STEP IN THE FOUNDATION ELEVATION, TYP.
- WALL FOOTING REINFORCING SHALL BE CONTINUOUS THROUGH PILASTER PAD FOOTINGS.
- BEFORE STARTING GRADING AND EXCAVATION, ESTABLISH THE LOCATION AND EXTENT OF UNDERGROUND UTILITIES IN THE WORK AREA. EXERCISE CARE TO PROTECT EXISTING UTILITIES DURING EARTHWORK OPERATIONS. PERFORM EXCAVATION WORK NEAR UTILITIES BY HAND AND PROVIDE NECESSARY SHORING AND SUPPORTS AS THE WORK PROGRESSES. SEE SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS REGARDING EXISTING UNDERGROUND UTILITIES. SEE MECHANICAL AND CIVIL/LANDSCAPE DRAWINGS FOR APPROXIMATE LOCATIONS OF EXISTING UTILITIES.
- ON THE FOOTING AND FOUNDATION PLAN, REFER TO VERBIAGE FOR FOOTING SIZES. DO NOT SCALE.
- SLOPE SLAB TO DRAINS WHERE INDICATED IN THE ARCHITECTURAL DRAWINGS.
- A 4" THICK GRANULAR BASE LAYER UNDER CLASS A VAPOR BARRIER UNDER THE NEW 4" CONCRETE SLAB ON GRADE IS DETAILED THROUGHOUT THIS SET OF CONSTRUCTION DOCUMENTS. IF THE FLOORING MANUFACTURER (B) RECOMMEND A THICKER LAYER OF GRANULAR MATERIAL OR A MORE STRINGENT TYPE OF VAPOR BARRIER, THEN THEIR RECOMMENDATIONS SHALL BE FOLLOWED. CONSTRUCTION MANAGER OR GENERAL CONTRACTOR TO COORDINATE.
- AT ALL RE-ENTRANT CORNERS IN THE SLAB, PLACE 2-#3 x 2'-6" LONG DOWELS @ 2" O.C. LOCATE BARS AT MID-DEPTH IN THE SLAB, TYPICAL.
- SEE DETAIL #6/S3.01 FOR MECHANICAL EQUIPMENT BASE DETAIL. SEE SHEET ARCHITECTURAL & MECHANICAL SHEETS FOR EXACT LOCATIONS OF EQUIPMENT BASES.
- SLAB CONTROL JOINTS. SEE SHEET A1.12 FOR LAYOUT PLAN.

SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska


CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary


Footing & Foundation Plan

S1.01



1 TYPICAL STOOP DETAIL


SCALE: 3/4" = 1'-0"



- NOTES:
1. PROVIDE 30# FELT BETWEEN BASE & FLOOR. BASE SHALL BE DOWELED TO FLOOR.
 2. ALL BASES SUPPORTING BOTH EQUIPMENT AND A CONCRETE INERTIA PAD TO BE REINFORCED AS FOLLOWS: - PROVIDE #4 REBAR @ 12" O.C. BOTH WAYS IN BASE.
 3. ADJUST SIZE AS REQUIRED FOR INDIVIDUAL EQUIPMENT INSTALLED.
 4. COORDINATE SIZE AND LOCATION WITH MECHANICAL CONTRACTOR.


6 MECHANICAL EQUIPMENT BASE

SCALE: NO SCALE




11 FOUNDATION SECTION

SCALE: 3/4" = 1'-0"




15 FRAMING SECTION

SCALE: 3/4" = 1'-0"




2 TYPICAL HORIZONTAL BAR BENDING

SCALE: 3/4" = 1'-0"




7 TYPICAL FOOTING STEP DETAIL

SCALE: 3/4" = 1'-0"




3 TYPICAL CMU WALL PLAN DETAIL

SCALE: 3/4" = 1'-0"




8 FOUNDATION SECTION

SCALE: 3/4" = 1'-0"




4 CONCRETE WALL CONSTRUCTION JOINT

SCALE: 3/4" = 1'-0"




9 FOUNDATION SECTION

SCALE: 3/4" = 1'-0"



5 CONTROL JOINT DETAIL

SCALE: 3/4" = 1'-0"



10 FOUNDATION SECTION

SCALE: 3/4" = 1'-0"

12 NOT USED


SCALE: NONE

13 NOT USED

SCALE: NONE


14 NOT USED

SCALE: NONE




17 FRAMING SECTION

SCALE: 3/4" = 1'-0"



18 FRAMING SECTION

SCALE: 3/4" = 1'-0"



SHEET HISTORY:
ISSUED 05/15/2023 CONSTRUCTION DOCUMENTS

Clark & Enersen, Inc.
Architecture Contact: Tim Ripp
Engineering Contact: TJ Schirmer
1010 Lincoln Mall, Suite 200
Lincoln, NE 68508
COA No. CA0029AE

Sidney West-Bound Rest Area

Sidney, Nebraska

CE No.: 508-020-21
NDOT No.: NH-80-2(92)
Control No.: 51276A
May 15, 2023



Preliminary

Structural Details

S3.01